



Male Disconnects – Heat Shrink Nylon Fully Insulated Butted Seam


Product Number†	UPC (054007-)	Wire Range (AWG)	Male Tab Width(W') x Thickness	L	W	D	Barrel Length	Barrel I.D.	Terminals per:	
									Bag	Case
MNHU18-250DMIX	06356	22-18	0.250 x 0.032	1.2	0.44	0.30	0.25	0.065	25	100
MNHU18-250DMIK	06357	22-18	0.250 x 0.032	1.2	0.44	0.30	0.25	0.065	—	250
MNHU14-250DMIX	06340	16-14	0.250 x 0.032	1.2	0.44	0.30	0.25	0.085	25	100
MNHU14-250DMIK	06341	16-14	0.250 x 0.032	1.2	0.44	0.30	0.25	0.085	—	250
MNHU10-250DMIX	06316	12-10	0.250 x 0.032	1.2	0.47	0.39	0.25	0.150	25	100
MNHU10-250DMIK	06317	12-10	0.250 x 0.032	1.2	0.47	0.39	0.25	0.150	—	250



MNHU18-250DMI
22-18
Suggested Mate: MNHU18-250DFI



MNHU14-250DMI
16-14
Suggested Mate: MNHU14-250DFI



MNHU10-250DMI
12-10
Suggested Mate: MNHI10-250DFI

Wire Range
Suggested Mate