


HOW TO ORDER BOARD LEVEL SHIELDING

The chart below is an easy-to-use reference on how Orbel BLS part numbers are created and used to order standard and custom board level shielding. Custom configurations that fall outside of our standard shield styles are also available.

Sample Part Number (Snap-Shield Bullzeye[™]): B-0750TB1125-0250XF - TPS



STANDARD FEATURES

PIN OPTIONS





Alignment Pin

Through-Hole Pin



Through-Hole Pin with Standoff



Castellation Edge

Straight Edge, No Pin

CORNER OPTIONS






Tight Corner

Louvered Corner



Welded Corner

ADDITIONAL OPTIONS



PERFORMANCE SPECS

Material Options

- Nickel Silver
- TPS: Tin-Plated Steel
- TPB: Tin-Plated Brass
- TPC: Tin-Plated Copper

Co-Planarity

- Smaller Shields: 0.004"
- Larger Shields: 0.008"

Material Thicknesses

- 0.010" (Standard)
- 0.008"
- 0.012"
- 0,015

- **RoHS-Compliant** Yes **Shielding Effectiveness**
 - Up to 60dB

Other material options include beryllium copper, phosphorus bronze, and stainless steel. Additional plating finishes available upon request.

All technical data presented herein is accurate to the best of our knowledge based on Orbel's most up-to-date testing information and material specs. This information is not presented as a warranty or guarantee and is not intended to be all-inclusive as to conditions of use.

5