





Rev	AWO #	Description	Date	Appr
-		RELEASED	04/10/12	

APPROVED: _____
 DATE: _____ TITLE: _____



DESCRIPTION	MATERIAL	FINISH
GASKET	RUBBER	ORANGE
RETAINING RING	SK-5	NICKEL
SPRING	SK-5	NICKEL
WASHER	IRON	NICKEL
SHELL	BRASS	NICKEL
FERRULE	BRASS	NICKEL
DIELECTRIC	TEFLON	NONE
PIN	BRASS	GOLD
BODY	BRASS	NICKEL

SPECIFICATIONS:

Frequency range: DC-4 GHz
 Nominal Impedance: 50 OHMS
 Working Voltage: 500 VOLTS max.
 Dielectric Withstanding Voltage: 1500 VRMS min.
 Temperature Rating:
 Operating temperature: -65°C to +165°C
 Environmental:
 Lead free, RoHS compliant.

UNLESS OTHERWISE SPECIFIED
 ALL DIMENSIONS ARE INCHES [MM]
 TOLERANCES: EXCEPT AS NOTED
 INCHES HOLES
 .X ± .10 Ø.X ± .10
 .XX ± .020 Ø.XXX ± .015
 .XXX ± .015 Ø.XXXX ± .010

ADAM TECH
 909 Rahway Avenue, Union, NJ 07083
 Phone: 908-687-5000 Fax: 908-687-5710

APPROVALS	DATE	TITLE
DRAWN TW	04/10/12	BNC CONNECTOR, 50 OHMS, RG174
CHECKED AY	04/10/12	
APPROVED		

SIZE	PART NO.	REV.
X	RF1-03-T-02-50	
REF: S00011T	SCALE: NTS	SHEET 1 OF 1

