

Twin Turbo Series TLHW-V88Y-930-SS



More Information



Specifications

Mounting Panel Mount with Volume Control

Color Yellow

Operating Mode Slow Warble Tone

 Operating Voltage
 9-30 Vdc

 Operating Frequency
 2900±250 Hz

 Typical Operating Current
 110 mA at 9 Vdc 50 mA at 30 Vdc

Typical Sound Pressure $85 \pm 5 \text{ dB(A)}$ at 9 Vdc at 24 inches (61 cm), at 25°C $103 \pm 5 \text{ dB(A)}$ at 30 Vdc at 24 inches (61 cm), at 25°C

Termination Ouick Connect Blades with Screws

Termination Strength Pull test with a maximum of 22 pounds (10 kg) load

Operating Temperature -20_C to +65_C Storage Temperature -40_C to +85_C

Surge Voltage 20% over maximum rated voltage for less than 5 minutes

Reverse Voltage Protection To the maximum operating voltage

Construction Materials Lens/Case- Yellow Translucent Polycarbonate 94 VO

Potting- 2 parts epoxy resin or silicone, black

Gasket Gasket (Included) 0.125" thick, 60 Durometer Neoprene

ASTM B117 Certified - Withstands exposure to salt spray for 300 hours IP 68 Certified - Withstands water submergence and dust exposure

Construction Materials

Humidity- 95% relative humidity at +40 C continuously for 100 hours.

Vibration- Withstands vibration between 0 and 55 Hz. on all axes.

Life Expectancy 10 years under normal operating conditions.

Warranty For a period of two years from the date of manufacture under normal operating conditions.

Notes This product is not intended as a life safety device.

Terms and Conditions of Sale Link here

Dimensions

