

# Product data sheet

Specifications



## Limit switch, L100/300, 600 V 10amp type I +options

L100WNS2M26

### Main

Range of product	L100/300
Series name	Severe duty mill
Product or component type	Limit switch
Product specific application	Mill switch
Device short name	L100 L300
Body type	Fixed
Head type	Rotary head
Sale per indivisible quantity	1

### Complementary

Base plate style	Style 2
Body material	Cast aluminium
Fixing mode	By the body
Type of operator	spring return without operating lever
Contact sequence number	26
Function available	Neutral position
Switch actuation	CW and CCW From left or right
Type of approach	Lateral approach
Electrical connection	Screw-clamp terminals AWG 22...AWG 12
Cable entry	1 entry for 1/2" - 14 NPT conforming to ANSI B1.20.1
Number of poles	2
Contacts type and composition	2 NO
CW operation contacts	1 NC + 1 NO
CCW operation contacts	1 NC + 1 NO
Contacts style	D
Switch function	DPST-NO-DB
Contact form	Form XX
Contacts material	90/10 AgCdO on copper backing stationary contact Silver on steel backing moveable contact

<b>Contacts usage</b>	-
<b>Contact operation</b>	Snap action
<b>Positive opening</b>	Without
<b>Minimum torque for tripping</b>	170 ozf.in
<b>Maximum actuation speed</b>	90 ft/min with 45° cam angle, levers only 130 ft/min with 30° cam angle, levers only
<b>Tripping angle</b>	9 °
<b>Maximum displacement angle</b>	70 °
<b>Repeat accuracy</b>	+/- 0.03 %
<b>Contact code designation</b>	A600, AC (Ue = 600 V) Ie = 5 A conforming to NEMA rating designation A600, AC (Ue = 480 V) Ie = 6.25 A conforming to NEMA rating designation A600, AC (Ue = 240 V) Ie = 12.5 A conforming to NEMA rating designation A600, AC (Ue = 120 V) Ie = 20 A conforming to NEMA rating designation P600, DC (Ue = 600 V) Ie = 0.2 A conforming to NEMA rating designation P600, DC (Ue = 250 V) Ie = 1 A conforming to NEMA rating designation P600, DC (Ue = 120 V) Ie = 5 A conforming to NEMA rating designation
<b>[Ithe] conventional enclosed thermal current</b>	20 A
<b>[Ui] rated insulation voltage</b>	600 V (pollution degree 3) conforming to IEC 60947-1 600 V (pollution degree 3) conforming to UL 508 600 V (pollution degree 3) conforming to CSA C22.2 No 14
<b>[Uimp] rated impulse withstand voltage</b>	2.5 kV AC for 1 minute conforming to CE 2.2 kV AC for 1 minute conforming to UL 2.64 kV AC for 1 minute conforming to CSA
<b>Short-circuit protection</b>	20 A Bussmann class CC KTK-R-20 non-time delay
<b>Width</b>	57.15 mm
<b>Height</b>	125.73 mm
<b>Depth</b>	86.61 mm
<b>Net weight</b>	0.68 kg
<b>Terminals description ISO n°1</b>	(3-4) right side contact (1-2) left side contact

## Environment

<b>Shock resistance</b>	30 gn for 9 ms conforming to IEC 60068-2-27
<b>Vibration resistance</b>	10 gn (f= 10...55 Hz) conforming to IEC 60068-2-6
<b>NEMA degree of protection</b>	NEMA 1 conforming to Nema type 250 NEMA 2 conforming to Nema type 250 NEMA 4 conforming to Nema type 250 NEMA 12 conforming to Nema type 250 NEMA 13 conforming to Nema type 250
<b>IP degree of protection</b>	IP67 conforming to IEC 60529
<b>Electrical shock protection class</b>	Class 0 conforming to IEC 61140
<b>Ambient air temperature for operation</b>	-23...85 °C
<b>Ambient air temperature for storage</b>	-23...85 °C
<b>Protective treatment</b>	Corrosion resistant gray paint

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	5.842 cm
<b>Package 1 Width</b>	7.112 cm

---

<b>Package 1 Length</b>	12.954 cm
<b>Package 1 Weight</b>	693.996 g

---

## Offer Sustainability

---

<b>REACH Regulation</b>	<a href="#">REACH Declaration</a>
<b>EU RoHS Directive</b>	Not applicable, out of EU RoHS legal scope
<b>Environmental Disclosure</b>	<a href="#">Product Environmental Profile</a>
<b>California proposition 65</b>	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>

## Contractual warranty

---

<b>Warranty</b>	18 months
-----------------	-----------

## Recommended replacement(s)