

## 107V

### MINIATURE EPOXY POTTED AUDIO TRANSFORMER



Audio input, line matching and output transformers  
Epoxy potted in an attractive molded case, Pin type, P.C. board  
mount, (min. 0.187" length)

Rugged epoxy potted construction produces a completely  
sealed unit withstanding severe environmental conditions.

In some models where no center tap is present (on the secondary), pin 5 is omitted.

Secondary may be used as primary and primary as secondary.

Will withstand soldering for 10 sec. @ 260 degrees C, ambient temp. 85 degrees C max.



Power level: 150mw @ 150 Hz. to 50 Khz.

-Freq. range @ +0 dbm is 150 Hz. to 80 Khz. +/- 1.5db



-Freq. range @ +10 dbm is 150 Hz. to 80 Khz. +/- 1.5db

-Freq. range @ +20 dbm is 150 Hz. to 80 Khz. +/- 1.5db


-Freq. measurements with no D.C. saturation.

### ELECTRICAL SPECIFICATIONS


Characteristic	Typical
Input Impedance	25000 $\Omega$ CT
Output Impedance	600 $\Omega$ CT
Output Power	0.150 Watts
DCR	
Primary 1-3	1400 $\Omega$ (805 $\Omega$ /595 $\Omega$ )
Secondary 4-6	66 $\Omega$ (33 $\Omega$ /33 $\Omega$ )
Inductance	@ 1.0 kHz, 1.0 V OC
Primary	33.5 Hy
Secondary	1.08 Hy
Impedance	@ 1.0 kHz, 1.0 V OC
Primary	131 K $\Omega$
Secondary	3.79 K $\Omega$
Frequency Response	$\pm$ 1.5db from 300Hz to 50KHz
Turns ratio	6.45:1
Dielectric Strength	100 Vrms
Temperature Range	-40 To 105°C**




### SCHEMATIC DIAGRAM




### PCB LAYOUT




### 107V Rs=25K RI=600 Frequency Response




### 107V Rs=25K, RI=600 THD+N



### 107V Rs=25K, RI=600 Phase Shift



### TYPICAL TEST CIRCUIT



Measurement instruments  
 Hp4192a impedance analyzer  
 Hp3456a DVM  
 Keithley 2002 DVM  
 D scope series iii audio analyzer

\*\* The epoxy that is used to cast these parts has a workable temperature range of  $-40^{\circ}\text{C}$  to  $+105^{\circ}\text{C}$   
 Under a normal rate of change, this does not include thermal shock.  
 Variations in the transformer materials and environmental conditions may reduce the workable temperature range.

This drawing and the information in it is the property of Hammond Manufacturing. It may not be reproduced, transmitted or used in any manner whatsoever without the written permission of Hammond Manufacturing. Data subject to change without notice.