



- NOTES:**
- JACK FOR MATING WITH SHIELDED PLUG (MOLEX 95043 AND 85568 SERIES).
  - PRODUCT SPECIFICATION : PS-95122.
  - APPLICATION SPECIFICATION : AS-95001.
  - PACKAGING SPECIFICATION: PK-95122 SHEET 2 (BLISTER PACKAGING ON REEL)
  - P.C. BOAR THICKNESS : (1.57) / .062
  - COPLANARITY OF SIGNAL LEADS: 0.10 MAX.

**TECHNICAL SPECIFICATIONS:**

**MATERIAL :**

HOUSING: POLYAMIDE GLASS FILLED UL 94V0, COLOR BLACK.

TERMINAL : PHOSPHOR BRONZE PLATED WITH : (0.00127) / .000050 MIN GOLD IN CONTACT AREA, (0.00190) / .000075 MIN PURE TIN IN TAIL AREA, BOTH OVER (0.00127) / .000050 MIN NICKEL OVERALL.

SHIELD : BRASS PLATED WITH (0.0020) / .000078 MIN TIN.

ENTER DESCRIPTION EC NO: MG2005-0122 DRAWN:KNOLLER 2004/10/08 CHKD:FCARABET 2004/10/08 APPR:KNOLLER 2004/10/08	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE		SCALE 4:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	
		mm	INCH	MM/IN	MM/IN			DATE	TITLE
REV K	DESCRIPTION	4 PLACES	± ---	± ---	DRAWN BY	03/07/28	FULLY SHIELDED SMT R/A MODULAR JACK 8 CKTS	molex	MOLEX INCORPORATED
		3 PLACES	± ---	± .010	CHECKED BY	03/07/28			
		2 PLACES	± 0.25	± .014	APPROVED BY	03/07/28			
		1 PLACE	± 0.35	± ---	DATE	03/07/28			
		ANGULAR ± 2 °		MATERIAL NO.		DOCUMENT NO.			
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE CHART		SDA-95122		2 OF 3		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION	