MATERIAL	PLATING	NOM. PLATING WT. (GRS)	VENDOR
BeCu	Ag/Cu	Ag=.017; Cu=.0087	FORMCO

PLATE FUSE CLIP 124016-2 AS FOLLOWS:

COMM BRIGHT SILVER .0001" MIN
OVER .00005" MIN COPPER FLASH

NO	COMPONENT NO	DESCRIPTION	QTY/M	U/M
-	PS001034	CYANIDE COPPER	0.024	LB
-	095400	SILVER PLATE	1.600	TOZ
-	124016-2	FUSE CLIP	1000	EA

BILL OF MATERIAL

UNLESS OTHERWISE SPECIFIED, DIMENSIONS DO NOT INCLUDE PLATING.

○	DENOTES CRITICAL CHARACTERISTICS.
CPK	DENOTES CPK DIMENSIONS,-MINIMUM CPK VALUE
⟨ST⟩	DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS.
CP	DENOTES CP DIMENSIONS,-MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE.

LTR	REVISION	CHK	APD
G	85458D-ADDED CHART 4/19/07 RP		
F	82565D-REVISE &REDRAW 10/15/02 TRG		

COPIES TO

1 9 18
2 10 19
3 12 20
4 13 21
5 14 23
6 15 33
7 16 43
8 17 53

MATL SPEC		FINISH
DRW TRG	DATE 10/15/02	SCALE NONE
CHK	DATE	SUPER DRW
APPD	DATE	RAW STK WT LBS/M

TOLERANCE UNLESS OTHERWISE SPECIFIED
TWO PLACE DEC ±.01 FRACTION ±
THREE PLACE DEC ±.005 ANGULAR ±1°

TITLE

FUSE CLIP

Littelfuse®
DES PLAINES, ILLINOIS 60016

REVISION	DRWG. NO.	
G	01230002Z	FINAL

CAD GENERATED DRAWING - NO PENCIL CHANGES ALLOWED