MINIATURE ENCAPSULATED TELECOMMUNICATION HIGH IMPEDANCE TRANSFORMER REV. Status A. Electrical Specifications (@ 25°C) REVISION -1. Primary Impedance; $30k\Omega$ 06/10/03 MP 2. Secondary Impedance; $30k\Omega$ REVISION A ADDED "H" TO 3. Primary Inductance; 30H MIN @ 200Hz, 10mVrms, Lp PART NUMBER Measured (1-3)08/27/03 MP 4. Leakage Inductance; 80mH MAX @ 1kHz, 10mVrms, (67mH TYP) Measured (1-3) with 6 & 4 shorted REVISION B **CHANGED** 5. DC Resistance; **DIMENSIONS** $(1-3):165\Omega \pm 15\%$ 03/10/04 MP $(6-4):165\Omega \pm 15\%$ REVISION C 6. Turns Ratio; $(1-3):(6-4)=1:1.00 \pm 2\%$ ADDED ROHS & UL #E208555 REFLOW NOTE Country 7. Core Loss; $110k\Omega$ MIN @ 200Hz, 10mVrms, Rp 05/15/07 MP of origin Measured (1-3)REVISION D **REPLACED** 8. Dielectric Strength; 1875Vrms 1 second @ Pri-Sec White dot-(RMIRA REFLOW NOTE 10.502Th indicates WITH GRAPH pin 1 11/13/07 MP B. Marking; TTC-5027H, TAMURA, date code and country of origin REVISION E "H" designates Safety Agency approved family classification. REVISED TEMP RATING Date C. Safety: Certified to UL60950, EN60950 Code 06/08/15 MP 3 D. Schematic; NOTE: Board washing is not recommended for these parts. 30KΩ Temp(°C) 210°CMA 200 E. Operating Temperature: -20 to $+85^{\circ}$ C 160°C 150 140°C Storage Temperature: -20 to +85°C 200°C MIN 20~25Sec 100 F. Suggested Reflow Profile (Terminal) Customer to determine proper profile based 40~50Sec. 45 Sec on actual conditions. 100 300 Time(Sec) G. Mechanical Specifications and Suggested Pad Layout; -1.30±0.10[0.051±0.004] — 9.60±0.25[0.378±0.010] Optional tape/label wrap; 4 sides 14.50±0.25 [0.571±0.010] 0 $2.50\pm0.25[0.098\pm0.010]$ -0.60[0.023]TYP -2.54[0.100]TYP 2.54±0.25[0.100±0.010] 7.60[0.299]MAX $12.50\pm0.25[0.492\pm0.010]$ $-0.60\pm0.5[0.023\pm0.020]$ 0.30[0.012]TYP PREPARED BY: C. POPPE 1.10[0.043]TYP-**ENGINEER:** DRAWING CONTROL NO. REV MODEL DESCRIPTION MODEL SPECIFICATION TELECOMMUNICATION MATHI P. P-A1-13174 F MODEM TRANSFORMER TTC-5027 SAFETY ENGINEER CONTENTS OF THIS DRAWING ARE SUBJECT TO CHANGE WITHOUT TAMURA CORPORATION OF AMERICA 1040 SOUTH ANDREASEN DRIVE, #100 ESCONDIDO, CA. 92029 (951) 699-1270 FAX 7607400536 DIM: mm[ln] SCL: 2/1 APPROVED: PROPRIETARY NOTICE: THIS DRAWING PRINT OR DOCUMENT AND SUBJECT MATTER DISCLOSED HEREIN ARE PROPRIETARY ITEMS TO WHICH TAMURA RETAINS THE EXCLUSIVE RIGHT OF DISSEMINATION, REPRODUCTION, MANUFACTURE AND SALE. THIS DRAWING, PRINT OR DOCUMENT IS SUBMITTED IN CONFIDENCE FOR CONSIDERATION BY THE RECIPIENT ALONE UNLESS PERMISSION FOR FURTHER DISCLOSURE IS EXPRESSLY GRANTED IN WRITING. M. PITCHAI