

## 623 Receptacle

**speedtec** - ready

12-pin insulation insert Code 0° housing code 1 flange mount /Flange 25x25 Anti-vibration o-ring

## **Technical Data**

number of pins

temperature range -20 °C to 130 °C

when connected IP 66/67 protection type

**Electrical Data** signal rated voltage

max. 7 A\* 160 V (AC/DC) 2500 V rated insulation voltage (L-L)

mating cycles 500

## Data according to VDE 0110/EN61984, Paragraph 6.19.2.2

pollution degree over voltage category 3 III max. height for operation 2000 m

Material

zinc diecast / nickel plated housing

insulation insert PBT, UL 94 / V0

seals Contacts (not part of product contents)

Tools (not part of product contents)

A EG A 175 NN 00 00 0201 000 A E A 175 N 00 00 0201 000



**Contact Arrangement** mating view



© 2018 TE Connectivity


TE Connectivity, TE connectivity (logo), intercontec (logo) and speedtec

While TE Connectivity (TE) has made every reasonable effort to ensure the accuracy of the information in this presentation, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this article are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.

TE Connectivity Industrial GmbH Bernrieder Straße 15 94559 Niederwinkling, Deutschland Tel.: +49 9962 2002-0 Fax: +49 9962 2002-70 E-Mail: intercontec@te.com

Web: www.intercontec.biz





<sup>1)</sup>Bei Bohrung M3 Sonderschraube mit d\u00fcnnem Kopfdurchmesser verwenden, siehe Zubeh\u00f6r! Alternativ auch Gewinde M2,5 m\u00f6glich

**Main Dimensions** Receptacle

\*for max. wire cross-section pay attention to the cross-section of used contacts