



RATED VOLTAGE: 120 VAC, 60 Hz
 ROTATION: CCW
 NO LOAD SPEED: 4.3 RPM
 NO LOAD CURRENT: 0.67 A

LOADED SPEED @ 90 IN-LB: 4.0 RPM
 LOADED CURRENT @ 90 IN-LB: 0.70 A
 STALL TORQUE: 160 IN-LB
 STALL CURRENT: 0.88 A

THERMALLY PROTECTED, PER UL E92971, CSA 48508

I/WE CERTIFY THAT SAMPLES OF THIS MOTOR HAVE BEEN FULLY TESTED BY THE UNDERSIGNED AND THAT ALL SPECIFICATIONS HAVE BEEN REVIEWED FOR PRODUCTION. MULTIPRODUCTS COMPANY, INC. IS NOT RESPONSIBLE FOR MOTORS THAT FAIL IN THE FIELD DUE TO INSUFFICIENT TESTING OF THE SAMPLE MOTORS.

I/WE AGREE TO PROVIDE MULTIPRODUCTS COMPANY, INC. WITH CURRENT DRAWINGS AND IN-HOUSE TEST PROCEDURES AS THEY BECOME AVAILABLE. ANY CHANGES THAT I/WE MAY MAKE WHICH OCCUR AFTER THE DATE SHOWN ARE SUBJECT TO REVIEW AND MAY AFFECT UNIT PRICE AND/OR DELIVERY DATES.

A	Ø.375/.374 WAS Ø.3750/.3745	2/19/2016	3199
REV.	DESCRIPTION	DATE	ECO#

TOLERANCES

- X.XX: ±.010
- X.XXX: ±.005
- FRACTION: ±1/64
- ANGLE: ±2°

UNLESS OTHERWISE SPECIFIED



MULTI PRODUCTS
 Company, Inc.

PART NAME/DESCRIPTION: **MULTIPRODUCTS**

DRAWN BY: DAB	DATE: 1/19/2015	SCALE: 0.75:1	MATERIAL: -
CHK'D BY: DMR	DATE: 1/19/2015	PART NUMBER: MOD-UL52-9904A	
APPR'D BY: RP	DATE: 1/19/2015		

SIGNATURE _____ PRINT NAME _____ DATE _____
 IN ORDER TO BEGIN PRODUCTION, MULTIPRODUCTS COMPANY, INC. MUST HAVE SIGNED APPROVAL.