# **Product data sheet**

Specifications





## Telequick mounting plate for PLA enclosure H500xW750mm

NSYPMR57

п	M	78	$\sim$	-	۰

Range	Thalassa
Accessory / separate part category	Mounting accessory
Product or component type	Mounting plate
Device application	Multi-purpose
Enclosure nominal dimensions	-
Mounting location	Back inserts Step slide
Mounting plate description	Telequick perforated
Range compatibility	Thalassa (Thalassa PLA)
Device composition	1 mounting plate
Material	Galvanised steel

#### Complementary

Fixing mode	By screws - screw type M8 - on back inserts location
Permanent permissible load	150 kg
Height	500 mm nominal: 370 mm real:
Width	750 mm nominal: 626 mm real:
Depth	15 mm real:
Cut-out dimensions	11 x 26 mm

#### **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.0 cm
Package 1 Width	37.0 cm
Package 1 Length	64.0 cm
Package 1 Weight	1.832 kg
Unit Type of Package 2	PAM
Number of Units in Package 2	72

Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 2 Height	50.0 cm	
Package 2 Width	100.0 cm	
Package 2 Length	120.0 cm	
Package 2 Weight	145.0 kg	

## Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

## **Contractual warranty**

Warranty 18 months

Recommended replacement(s)