

RSL1PRJU

Harmony, Slim interface relay pre-assembled, 6 A, 1 CO, with LED, with protection circuit, spring terminals, 12 V AC/DC



Main

| | |
|--|---|
| Range of Product | Harmony Electromechanical Relays |
| Series name | Interface relay |
| Product or Component Type | Pre-assembled plug-in relay with socket |
| Device short name | RSL |
| Contacts type and composition | 1 C/O |
| Contact operation | Standard |
| [Uc] control circuit voltage | 12 V DC |
| [Ithe] conventional enclosed thermal current | 6 A -40...131 °F (-40...55 °C) |
| Status LED | With |
| Shape of pin | Flat (PCB type) |

Complementary

| | |
|--|---|
| Fixing Mode | Plastic compression spring |
| Average resistance | 848 Ohm DC 23 °C +/- 10 % |
| [Ui] rated insulation voltage | 250 V EN/IEC 277 V cUL |
| [Uimp] rated impulse withstand voltage | 6 kV IEC |
| Contacts material | Silver alloy (AgSnO2) |
| [Ie] rated operational current | 6 A 1 C/O AC-1/DC-1)IEC/UL |
| Minimum switching current | 100 mA |
| Maximum switching voltage | 277 V |
| Minimum switching voltage | 12 V |
| Maximum switching capacity | 1500 VA 150 W |
| Minimum switching capacity | 120 mW |
| Operating rate | <= 72000 cycles/hour no-load <= 360 cycles/hour under load |
| Mechanical durability | 10000000 cycles |
| Electrical durability | 60000 cycles resistive, 6 A 250 V, AC-1 |
| Operating time | 5 ms reset 12 ms |
| Marking | CE |
| Protection category | RT III |
| Test levels | Level A |
| Operating position | Any position |
| Height | 3.09 in (78.6 mm) |
| Width | 0.24 in (6.2 mm) |
| Depth | 3.98 in (101 mm) |
| Terminals description ISO n°1 | (A1-A2)CO (11-12-14)OC |
| Sale per indivisible quantity | 10 |
| Net Weight | 0.06 lb(US) (0.029 kg) |
| Load current | 6 A 250 V AC 0.5 mm mounting distance |
| Average coil consumption | 0.17 W, DC |

| | |
|------------------------------|--|
| Drop-out voltage threshold | >= 0.05 Uc |
| Contact terminal arrangement | Separate |
| Connections - terminals | Spring terminals, 1 x 0.2...1 x 1.5 mm ² AWG 24...AWG 16) flexible with cable end Spring terminals, 1 x 0.2...1 x 1.5 mm ² AWG 24...AWG 16) solid without cable end |
| Safety reliability data | B10d = 60000 |
| Clamping force | 10...40 N |
| Control Type | Without push-button |
| Mounting Support | 35 mm symmetrical DIN rail |
| Device presentation | Complete product |

Environment

| | |
|---------------------------------------|--|
| Input voltage | 12 V AC/DC 11.4...14.4 V) |
| Dielectric strength | 1000 V AC between contacts 4000 V AC between coil and contact |
| Standards | CSA C22.2 No 14 UL 508 EN/IEC 61810-1 |
| Product Certifications | CSA UL GOST |
| Ambient Air Temperature for Storage | -40...185 °F (-40...85 °C) |
| Vibration resistance | 10 gn +/- 1 mm 10...150 Hz)10 cycles not operating EN/IEC 60068-2-6 5 gn +/- 1 mm 10...150 Hz)10 cycles in operation EN/IEC 60068-2-6 |
| IP degree of protection | IP40 conforming to EN/IEC 60529 |
| Shock resistance | 10 gn 11 ms) in operation EN/IEC 60068-2-27 5 gn 11 ms) not operating EN/IEC 60068-2-27 |
| Ambient air temperature for operation | -40...131 °F (-40...55 °C) |

Ordering and shipping details

| | |
|-----------------------|-------------------------------|
| Category | 21127 - ZELIO ICE CUBE RELAYS |
| Discount Schedule | CP2 |
| GTIN | 3606480077890 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 1.09 oz (31 g) |
| Returnability | No |
| Country of origin | CN |

Packing Units

| | |
|------------------------------|--------------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 3.35 in (8.5 cm) |
| Package 1 width | 2.76 in (7 cm) |
| Package 1 Length | 4.21 in (10.7 cm) |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 10 |
| Package 2 Weight | 11.11 oz (315 g) |
| Package 2 Height | 3.35 in (8.5 cm) |
| Package 2 width | 2.76 in (7 cm) |
| Package 2 Length | 4.21 in (10.7 cm) |
| Unit Type of Package 3 | S03 |
| Number of Units in Package 3 | 300 |
| Package 3 Weight | 23.27 lb(US) (10.553 kg) |
| Package 3 Height | 11.81 in (30 cm) |
| Package 3 width | 11.81 in (30 cm) |
| Package 3 Length | 15.75 in (40 cm) |

Offer Sustainability

| | |
|----------------------------|--|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Dimensions

