

## EMC housing - HC-B 10-TFQ-70/O1STM32S-EMV - 1642399

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



HEAVYCON sleeve housing B10, for double locking latch, height 70 mm, with thread M32, lateral cable outlet, EMC version



### Key commercial data

Packing unit	1 PCE
Weight per Piece (excluding packing)	152.1 GRM
Custom tariff number	85389099
Country of origin	Czech Republic

### Technical data

#### Dimensions

Height	70 mm
Width	43 mm
Length	73 mm

#### Ambient conditions

Degree of protection of housing (IP)	IP65
Ambient temperature (operation)	-40 °C ... 100 °C

#### General

Note	For contact inserts HC-B10, BB18, DD42, M, K8/24
Design	B10
Housing type	Sleeve housings
Locking type	For double locking latch
No. of cable exits	1
Cable exit	Lateral
Screw connection	None
Type of the screw connection	1x M32

# EMC housing - HC-B 10-TFQ-70/O1STM32S-EMV - 1642399

## Technical data

### General

Housing material	Aluminum die-cast
Housing surface material	EMC coating, silver

## Classifications

### eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27140816
eCl@ss 5.0	27143424
eCl@ss 5.1	27143424
eCl@ss 6.0	27143424
eCl@ss 7.0	27440209
eCl@ss 8.0	27440209

### ETIM

ETIM 3.0	EC000437
ETIM 4.0	EC000437
ETIM 5.0	EC000437

### UNSPSC

UNSPSC 6.01	31261502
UNSPSC 7.0901	31261502
UNSPSC 11	31261502
UNSPSC 12.01	31261502
UNSPSC 13.2	31261502

## Accessories

### Accessories

#### Full screw connection

Cable gland - HC-EMV-KV-M32(11-21) - 1690529




EMC screw connection up to 5 bar, thread length: 9 mm, cable diameter: 11.0 - 21.0 mm, WAF 36, screw connection: M32

# EMC housing - HC-B 10-TFQ-70/O1STM32S-EMV - 1642399

## Drawings

Diagram



Shield attenuation

Dimensioned drawing

