



SITOP BATTERY MODULE/24V/7AH

SITOP battery module 24 V/7 Ah with maintenance free sealed lead batteries for SITOP DC UPS module 6 A, 15 A and 40 A \*Ex approval no longer available\*

Charging current charging voltage	
end-of-charge voltage at DC	
• at -10 °C recommended	29 V
• at 0 °C recommended	28.4 V
• at 10 °C recommended	27.8 V
• at 20 °C recommended	27.3 V
• at 30 °C recommended	26.8 V
• at 40 °C recommended	26.6 V
• at 50 °C recommended	26.3 V
Output	
charging current maximum	1.75 A
output voltage at DC rated value	24 V
Safety	
design of short-circuit protection	Battery fuse 20 A/32 V (solid-state circuitry blade-type fuse + support)
design of the overload protection	Valve control
Safety	
operating resource protection class	Class III
protection class IP	IP00
Approvals	
certificate of suitability	
• CE marking	Yes
• UL approval	Yes
• as approval for USA	cURus-Recognized (UL 1778, CSA C22.2 No. 107.1), File E219627
• cCSAus, Class 1, Division 2	No
• ATEX	No
certificate of suitability	
• EAC approval	Yes
• shipbuilding approval	Yes
shipbuilding approval	ABS, DNV GL
Marine classification association	
• American Bureau of Shipping Europe Ltd. (ABS)	Yes
• DNV GL	Yes
environmental conditions	
Operating data note	For storage, mounting and operation of lead-acid batteries, the relevant DIN/VDE regulations or country-specific regulations (e.g. VDE 0510 Part 2/EN 50272-2) must be observed. You must ensure that the battery site is sufficiently ventilated. Possible sources of ignition must be at least 50 cm away.
ambient temperature	
• during operation	-15 ... +50 °C

<ul style="list-style-type: none"> <li>• during transport</li> <li>• during storage</li> </ul>	-20 ... +50 °C
relative temporary capacity loss at 20 °C in a month typical	-20 ... +50 °C
	3 %
<b>Service life</b>	
service life of energy storage	capacity falls to 80 % of original capacity (according to EUROBAT)
<ul style="list-style-type: none"> <li>• typical</li> </ul>	4 y
<ul style="list-style-type: none"> <li>• at 20 °C typical</li> </ul>	2 y
<ul style="list-style-type: none"> <li>• at 30 °C typical</li> </ul>	1 y
<ul style="list-style-type: none"> <li>• at 40 °C typical</li> </ul>	0.5 y
<ul style="list-style-type: none"> <li>• at 50 °C typical</li> </ul>	
ambient temperature during storage	Along with the storage and operating temperature, other factors such as the duration of the storage period and the charge status during storage have a decisive influence on the possible useful life. Batteries should therefore be stored as briefly as possible, always fully charged, and within the temperature range 0 to +20 °C.
<b>Mechanics</b>	
type of electrical connection	spring-loaded terminals
<ul style="list-style-type: none"> <li>• for power supply unit</li> </ul>	1 screw terminal each for 0.08 ... 4 mm <sup>2</sup> for + BAT and - BAT
product component included	Accessories pack with solid-state circuitry fuse 20 A and 30 A
width of the enclosure	186 mm
height of the enclosure	168 mm
depth of the enclosure	121 mm
installation width	206 mm
mounting height	188 mm
fastening method	
<ul style="list-style-type: none"> <li>• wall mounting</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• standard rail mounting</li> </ul>	No
<ul style="list-style-type: none"> <li>• S7 rail mounting</li> </ul>	No
fastening method	can be screwed onto flat surface (keyhole mounting for hooking in to M4 screws)
net weight	6 kg
number of cells	12
battery capacity	7 A·h
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

