


NOTES:

1. ALL PARTS TO BE BULK PACKED
2. CONTACTS ARE ASSEMBLED WITH THE SOLDER CUPS FACING DIRECTLY OUTWARD
3. ALL DIMENSIONS ARE REFERENCE EXCEPT THOSE WITH A TOLERANCE

ASSEMBLY P/N	CONTACT QTY.		CABLE O.D. RANGE
	#16	#20	
W8C82-6PG-P-513	2	4	.13-.15 [3.3-3.8]
W8C82-6PG-P-516			.16-.18 [4.1-4.6]
W8C82-6PG-P-519			.19-.21 [4.8-5.3]
W8C82-6PG-P-522			.22-.25 [5.6-6.]
W8C82-6PG-P-526			.25-.27 [6.4-6.9]
W8C82-6PG-P-528			.26-.285 [6.6-7.2]



SHOWN ASSEMBLED
FOR CUSTOMER REFERENCE ONLY

DIMENSIONS IN BRACKETS [] ARE IN MILLIMETERS

CUSTOMER APPROVAL

THIS DOCUMENT CONTAINS CONFIDENTIAL INFORMATION PROPRIETARY TO CONXALL CORPORATION. ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS DOCUMENT /INFORMATION IS EXPRESSLY PROHIBITED UNLESS AUTHORIZED IN WRITING BY CONXALL CORPORATION.

APPROVED BY: _____
DATE: _____

RoHS COMPLIANT

MA	07-20-20	RELEASED PER PDR 16014-10
PNK	01-18-18	PDR16014
REV.	INIT.	DATE
A	MA	07-20-20
	PNK	01-18-18
DESCRIPTION		ORIG. DRAWN BY: PNK
ALL INFORMATION ILLUSTRATED IS THE PROPERTY OF "CONXALL CORPORATION". UNAUTHORIZED DUPLICATION OR DISTRIBUTION OF THIS DOCUMENT IS PROHIBITED.		DATE: 01-18-18
APPROVED BY:		CHECKED BY:
ALL UNITS ARE IN FEET, INCHES, FRACTION OF INCHES AND DECIMALS.		APPROVED BY:
UNLESS OTHERWISE SPECIFIED TOLERANCES: 3 PLACE DECIMALS ±.010 ANGLES ±1° FRACTIONS ±1/16		SCALE: NTS
- CRITICAL CHARACTERISTIC FLAG PER SPEC. XXXX		SIZE: B
FILE: W8C82-6PG-P-5XX	DIRECTORY: SLW	SHEET: 1 OF 1
TITLE: CABLE-TO-CABLE ASSEMBLY 2-16 + 4-20 PIN CONTACTS, SOLDER INSTA-CLICK™ MINI-CON-X POWER/SIGNAL		CUSTOMER: STANDARD PRODUCT
PART NUMBER: W8C82-6PG-P-5XX		REV: A



601 E. WILDWOOD VILLA PARK, IL 60181