NOTES:  I. MATERIALS OF CONSTRUCTION: SHELL, FERRULE & BODY = BRASS, NICKEL PLATED CONTACT PIN = BRASS, SILVER PLATED INSULATOR = PHENOLIC, YELLOW PER PANTONE 110C		83-85P-RFX  DRAWING NO. THIRD ANGLE PROJ.	REV A	REVISIONS  DESCRIPTION  RELEASE TO MFG.	PATE, ECO APPR 8/25/00 43482 CPM
30,6 REF - [1.21]				SCAL	_E 2.000
Ø 18.2 [.716]		Ø 7,4 Ø 9,3 [.366]	Ø 10,9 [.429]	[.622]	Ø 12,4 [.488]
	RECOMMENT STRIPPING SCALE	DED CABLE DIMENSIONS 3.000		CUSTOMER OUTLIN FOR REFERENC	1
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE:  0.5 - 6mm 6 - 30mm 30 - 120mm  ±0.2mm ±0.4mm ± 0.6mm  NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol Corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights or permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.	REFERENCE EAR 967604-0 GEN# ASSYM2_UHF	DRAWN C. McGRATH ENGINEER T. AUBIN APPROVED CAD FILE I:\UHF\83-8SP-RFX	0/10/00 1	CODE ID DWG SIZEDRAWING NO	Amphenol Corporation Communication and Network Products Division Danbury, CT U.S.A. 06810  SCALE: 4.0:1 SHEET 2 OF 2  3-8SP-RFX  REV A