

LM-7000H Series

Ethernet modules for PT-G7728/G7828 series switches

Specifications

LM-7000H Series



LM-7000H-4GTX



LM-7000H-4GSFP



LM-7000H-4GPoE

Note: See the SFP-1G and SFP-1FE datasheets for SFP module product information.

Interface

RJ45 Ports: 10/100/1000BaseT(X)

SFP Ports: 100/1000Base SFP

PoE Ports: 100/1000BaseT(X), IEEE 802.3af/at standards, Mode A

Power Requirements

Power Consumption:

LM-7000H-4GTX: 1.98 W

LM-7000H-4GSFP: 1.56 W

LM-7000H-4GPoE: 1.98 W (w/o PoE output)

Physical Characteristics

Weight:

LM-7000H-4GTX: 0.24 kg (0.53 lb)

LM-7000H-4GSFP: 0.3 kg (0.66 lb)

LM-7000H-4GPoE: 0.24 kg (0.53 lb)

MTBF (mean time between failures)

Time:

LM-7000H-4GTX: 2,641,729 hrs

LM-7000H-4GSFP: 2,475,903 hrs

LM-7000H-4GPoE: 1,280,518 hrs

Standard: Telcordia (Bellcore), GB

Warranty

Warranty Period: 5 years

Details: See www.moxa.com/warranty

Ordering Information

Compatible Ethernet Switch Systems

Ethernet Switch System:

PT-G7728/G7828



LM-7000H Series

Available Models	Port Interface		
	10/100/1000BaseT(X)	100/1000BaseSFP	PoE+ 10/100/1000BaseT(X)
LM-7000H-4GTX	4	–	–
LM-7000H-4GSFP	–	4	–
LM-7000H-4GPoE	–	–	4

Package Checklist

- LM-7000H series interface module
- Substance Disclosure table
- Product Certificate of Quality Inspection (Simplified Chinese)
- Product Notices (Simplified Chinese)
- Warranty card