Locking lever; for manual operation; black

www.wago.com/890-101



Color:

 $\label{thm:condition} \textbf{Subject to changes. Please also observe the further product documentation!}$

WAGO GmbH & Co. KG Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.

www.wago.com/890-101



Item description

Locking system WINSTA® MINI

The locking system from the *WINSTA*® MINI product line is the sophisticated solution for reliable electrical installation. You can rely on the quality of WINSTA® components from WAGO for your electrical installation accessories too. Due to its particularly minimal dimensions, our *WINSTA*® MINI Pluggable Connection System with Push-in CAGE CLAMP® spring pressure connection technology is especially suitable in very tight spaces, i.e., for installations when very little room is available.

Push-in CAGE CLAMP® spring pressure connection technology – pluggable installation instead of laborious screw connections!

WINSTA® is the pluggable connection system that is optimally tailored to the strict requirements of electrical installation. It allows error-free installation of cables and components, quickly and reliably. Enjoy the benefits of the pluggable version of our maintenance-free spring pressure connection technology too! Plan your installation with WINSTA® MINI accessories from WAGO.

- consistent IP40 protection
- fast, secure installation

Data

Connection data

Connection 1

Actuation type

Mechanical Data	
Suitable	for flying leads; manually operated

Finger-operated lever

Material Data

Note (material data)

Information on material specifications can be found here

Color	black
Insulation material	Polyamide (PA66)

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.

www.wago.com/890-101



Flammability class per UL94	VO
Fire load	0.019 MJ
Weight	0.6 g

Environmental requirements

Processing temperature	-5 +40 °C
Continuous operating temperature	-35 +85 ℃
Note on continuous operating temperature	Insulating parts for temperatures ≤ 105 °C

Commercial data

eCl@ss 10.0	27-44-06-92
eCl@ss 9.0	27-44-06-92
ETIM 8.0	EC002863
ETIM 7.0	EC002863
PU (SPU)	100 (50) pcs
Packaging type	box
Country of origin	DE
GTIN	4055143356930
Customs tariff number	85389099990

Environmental Product Compliance

Approvals / Certificates

Approvals for marine applications

			Certificate
Logo	Approval	Additional Approval Text	name
	LR	EN 61535	08/20047
	Lloyds Register		(E2)

Downloads Documentation

Bid Text

890-101 2019 年2月19 日 xml Download X81 - Datei 2.7 kB

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.

www.wago.com/890-101



890-101 2017 年4月13 日 doc Download doc - Datei 22.0 kB

CAD/CAE-Data

CAD data

2D/3D Models 890-101 URL Download

CAE data

ZUKEN Portal 890-101 URL Download

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 890-101 URL Download

Locking lever; for manual operation; black

Installation Notes

Product family

WINSTA® MINI

Show all products from the family

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.