



- Notes
- ① The recommended tightening torque of ref.No.① shall be 2 to 3N・m. LOCTITE 263, HENKEL JAPAN or equivalent is recommended to prevent ref. No. ① from loosening.
 - ② Across flats of hexagon hole of ref. No. ⑤ to be 1.27. The recommended tightening torque of ref.No.⑤ shall be 0.3 to 0.4N・m.
 - ③ The cable pull and twisting strength (, waterproof tightness) and other characteristics may differ, depending on the cable structure. please confirm before the use.

| | | | | | | | | | |
|-------|--------------------------|------------------|--------------------------|-----------------|------------------|----------|--|--|--|
| 3 | Chloroprene rubber | (Black) | | | | | | | |
| 2 | Brass | Nickel plating | 5 | Stainless steel | | | | | JIS 8 117T Hexagon socket set screw M2 EXD.45X2 |
| 1 | Brass | Nickel plating | 4 | Brass | Nickel plating | MSD.5X8 | | | JIS 8 1111 Pin head machine screw |
| NO. | MATERIAL | FINISH . REMARKS | NO. | MATERIAL | FINISH . REMARKS | | | | |
| UNITS | SCALE | COUNT | DESCRIPTION OF REVISIONS | DESIGNED | CHECKED | DATE | | | |
| mm | 2 : 1 | 1 | DIS-C-00007459 | TY. SUZUKI | HY. KOBAYASHI | 20211208 | | | |
| | APPROVED : HY. KOBAYASHI | | 20180222 | DRAWING NO. | EDC-112372-31-00 | | | | |
| | CHECKED : HY. KOBAYASHI | | 20180222 | PART NO. | RM24WTP-CP14(31) | | | | |
| | DESIGNED : HY. KISHI | | 20180222 | CODE NO. | CL0109-1851-9-31 | | | | |
| | DRAWN : MK. INOUE | | 20180208 | | | | | | |



APPROVED : HY. KOBAYASHI
 CHECKED : HY. KOBAYASHI
 DESIGNED : HY. KISHI
 DRAWN : MK. INOUE