

B1.

**Cable Ties** 

B2.

Cable Accessories

B3. Stainless Steel Ties

> C1. Wiring Duct

C2. Surface Raceway

C3. Abrasion

Protection

C4. Cable Management

> D1. Terminals

D2. Power Connectors

D3.

Grounding Connectors

E1.

Labeling Systems

E2.

Labels

E3.

**Pre-Printed** 

& Write-On

Markers

E4.

Permanent

Identification

E5.


Lockout/ Tagout & Safety Solutions

## ீரு 2x2 and 4x4 Fiber-Duct™ Routing Systems

- Channel, covers, fittings and other non-metallic system components made from V-0 flame class rated material
- Compatible with Panduit<sup>®</sup> FiberRunner<sup>®</sup>2x2, 4x4, 6x4 and 12x4 Routing Systems

Std Std

• Snap-on non-slip covers



S4X4

				m	1
	111	The	71	IIII	
		114	11		
1		11			

E2X2 E4X4

C2 C4

Part Number	Part Description	System Size	Pkg. Qty.	Ctn.
Fiber-Duct <sup>™</sup> Ch	nannel			
S2X2YL6NM	Used to carry the cables throughout the Fiber-Duct <sup>™</sup> Routing System. Accepts cover C2YL6. Cover sold separately.	2x2	6	120
S4X4YL6NM	Used to carry the cables throughout the Fiber-Duct <sup>™</sup> Routing System. Accepts cover C4YL6. Cover sold separately.	4x4	6	60
Fiber-Duct <sup>™</sup> Sl	otted Channel			
E2X2YL6	Used to carry the cables vertically to the front or the back of equipment racks throughout the system. Accepts cover C2YL6. Extra supports required when used in horizontal applications. Cover sold separately.	2x2	6	120
E4X4YL6	Used to carry the cables vertically to the front or the back of equipment racks throughout the system. Accepts cover C4YL6. Extra supports required when used in horizontal applications. Cover sold separately.	4x4	6	60
Fiber-Duct <sup>™</sup> Co	over			
C2YL6	Cover for Fiber-Duct <sup>™</sup> Channel and Fiber-Duct <sup>™</sup> Slotted Channel. Non-slip cover design incorporates integral high friction lining to inhibit cover movement.	2x2	6	120
C4YL6	Cover for Fiber-Duct <sup>™</sup> Channel and Fiber-Duct <sup>™</sup> Slotted Channel. Non-slip cover design incorporates integral high friction lining to inhibit cover movement.	4x4	6	120

Note: Available with mounting holes. To order, delete NM from the part number. For fastest installation use NR2WH-L or NR4BL-L snap rivets.

For other colors replace YL (Yellow) with OR (Orange) or BL (Black).

Order number of feet required, in multiples of standard 6' length increments.

## Fiber-Duct<sup>™</sup> System Fittings



FRA2X2

FRA4X4

Std. Std. System Pkg. Ctn. Part Number Part Description Size Qty. Qty. **Coupler Fitting** FCF2X2YL Used to join two sections of duct together. 2x2 1 5 Fiber-Duct<sup>™</sup> Coupler is not required at each FCF4X4YL 1 5 4x4 fitting connection. Horizontal Right Angle Fitting FRA2X2YL Attaches to channel to create a 90° horizontal turn 2x2 1 5 from a straight horizontal run. Cover included. FRA4X4YL 4x4 1 5

For other colors replace suffix YL (Yellow) with OR (Orange) or BL (Black). Fittings include 5/16" assembly holes for fast mechanical fastening.

F.	
Index	

**NDUIT<sup>®</sup>** ELECTRICAL SOLUTIONS

## Fiber-Duct<sup>™</sup> System Fittings (continued)



Part Number	Part Description	System Size	Pkg.	Std. Ctn. Qty.	B1. Cable Ties	
Horizontal Tee F	Fitting	1			B2.	
FT2X2YL	Attaches to channel to create a 90° horizontal	2x2	1	5	Cable Accessories	
FT4X4YL	branch from a straight horizontal run. Cover included.	4x4	1	5		
Four Way Cross	Fitting				B3. Stainless	
FFWC2X2YL	Attaches to channel to create a horizontal four way cross intersection. Cover included.	2x2	1	5	Steel Ties	
FFWC4X4YL		4x4	1	5	C1.	
End Cap Fitting					Wiring Duct	
FEC2X2YL	Used for closing off open ends of the channel.	2x2	1	5		
FEC4X4YL	No coupler required. Push-on installation.	4x4	1	5	C2. Surface	
nside Vertical 4	5° Angle Fitting				Raceway	
FIV452X2YL	Attaches to channel to create a 45° upward angle from a straight horizontal run. Used with outside	2x2	1	5	C3. Abrasion	
FIV454X4YL	vertical 45° angle fitting FOV452X2YL or FOV454X4YL to change level of straight horizontal runs. Cover included.	4x4	1	5	Protection	
<b>Dutside Vertical</b>	45° Angle Fitting				C4. Cable	
FOV452X2YL	Attaches to channel to create a 45° downward angle from a straight horizontal run. Used with inside vertical 45° angle fitting FIV452X2YL or	2x2	1	5	Management	
FOV454X4YL	FIV454X4YL to change level of straight horizontal runs. Cover included.	4x4	1	5	D1. Terminals	
nside Vertical F	Right Angle Fitting					
FIVRA2X2YL	Attaches to channel to create a 90° upward angle from a straight horizontal run. Used with outside vertical 90° angle fitting FOVRA2X2YL or	2x2	1	5	D2. Power Connectors	
FIVRA4X4YL	FOVRA4X4YL to change level of straight horizontal runs. Cover included.	4x4	1	5	D3.	
Outside Vertical	Right Angle Fitting	1			Grounding Connectors	
FOVRA2X2YL	Attaches to channel to create a 90° downward angle from a straight horizontal run. Used with inside vertical 90° angle fitting FIVRA2X2YL or	2x2	1	5		
FOVRA4X4YL	FIVRA4X4YL to change level of straight horizontal runs. Cover included.	4x4	1	5	E1. Labeling Systems	
4x4 to 2x2 Fiber	r-Duct™ Reducer Fitting	1				
FRF42YL	Joins any 4x4 Fiber-Duct <sup>™</sup> Fitting to the 2x2 Fiber-Duct <sup>™</sup> Channel, S2X2YL6 or E2X2YL6. Includes cover.	2x2 4x4	1	5	E2. Labels	
	ace suffix YL (Yellow) with OR (Orange) or BL (Black). assembly holes for fast mechanical fastening.				E3. Pre-Printed & Write-On Markers	
					E4.	

E4. Permanent Identification

A. System Overview

E5. Lockout/ Tagout & Safety Solutions

> F. Index