



SIMATIC ET 200SP, BaseUnit Type C1, BU20-P6+A2+4B BU type C1, Push-in terminals, with 2 AUX terminals, bridged to the left, WxH: 20 mmx117 mm

General information	
Product type designation	BU type C1
HW functional status	FS10 and higher
Supply voltage	
Rated value (DC)	See manual
<ul style="list-style-type: none"> <li>For P1 and P2 bus</li> <li>For AUX bus</li> <li>for process terminals</li> </ul>	24 V 24 V; Equal potential group to P1/P2 bus or PE 24 V
Rated value (AC)	See manual
<ul style="list-style-type: none"> <li>For P1 and P2 bus</li> <li>For AUX bus</li> <li>for process terminals</li> </ul>	230 V 230 V; Equal potential group to P1/P2 bus or PE 230 V
Mains filter	
<ul style="list-style-type: none"> <li>integrated</li> </ul>	No
Current carrying capacity	
up to 60 °C, max.	10 A
For P1 and P2 bus, max.	10 A
For AUX bus, max.	10 A
For process terminals, max.	5 A; 10 A for process terminals 5 and 6
Hardware configuration	
Automatic encoding	Yes
Slots	
<ul style="list-style-type: none"> <li>Number of slots</li> </ul>	1; Type C1
Potential separation	
between backplane bus and supply voltage	Yes
between process terminals and supply voltage	Yes
between power bus and supply voltage	No
Isolation	
Isolation tested with	3 100 V DC
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> <li>horizontal installation, min.</li> <li>horizontal installation, max.</li> <li>vertical installation, min.</li> <li>vertical installation, max.</li> </ul>	-30 °C 60 °C -30 °C 50 °C
Altitude during operation relating to sea level	
<ul style="list-style-type: none"> <li>Installation altitude above sea level, max.</li> </ul>	2 000 m; On request: Installation altitudes greater than 2 000 m
Accessories	
Color coding labels	

- for process terminals
- for AUX terminals
- for add-on terminals

CC51  
 CC84 to CC86  
 does not exist

#### connection method / header

##### Terminals

- |  |                               |
|--|-------------------------------|
| • Terminal type  | Push-in terminal              |
| • Conductor cross-section, min.                        | 0.14 mm <sup>2</sup> ; AWG 26 |
| • Conductor cross-section, max.                        | 2.5 mm <sup>2</sup> ; AWG 14  |
| • Number of process terminals to I/O module            | 16; Pro slot                  |
| • Number of terminals to AUX bus                       | 0                             |
| • Number of add-on terminals                           | 0                             |
| • Number of terminals with connection to P1 and P2 bus | 2; Pro slot                   |

##### Dimensions

Width	20 mm
Height	117 mm
Depth	35 mm

##### Weights

Weight, approx.	47 g
-----------------	------

**last modified:** 1/16/2021 