



NOTES:

1. METALSHELLS: STEEL; min. 315µin TIN over 40-80µin NICKEL
2. INSULATORS: PBTP GF UL 94 V-0, BLACK
3. CONNECTOR IS PART MARKED: 3043W2SXK99A10X CONEC ABC

Directive 2002/95/EC
„RoHS“
Compliant

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	
CUSTOMER APPROVAL DATE:	
NAME:	TITLE:
COMPANY NAME:	
APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH				tolerance		 dim. in mm	scale: 2:1	
				DO NOT ALTER CAD DRAWING BY HAND			material: SEE NOTES	
a	Origin			drawn	12.06.08	name	D-SUB COMBINATION FEMALE 43W2S CRIMP STYLE	
rev.	description	date	name	appd.	13.06.08	Mickenbecker		
				norm				
				d-old				
CONEC ®				dwg no:	Inventor 10		DIN-A3	
				13K1A2527		sh: 1		
				part no:		3043W2SXK99A10X		