



SPECIFICATION FOR APPROVAL

Customer : DPC

Description : DC FAN

Customer Part No. _____

REV. : _____

Delta Model No. : QFR1212GHEEVT

REV. : 03

Sample Issue No. : _____

Sample Issue Date : OCT.25 2019

PLEASE SEND ONE COPY OF THIS SPECIFICAITON BACK AFTER YOU SIGNED APPROVAL FOR PRODUCTION PRE-ARRANGMENT.

APPROVED BY:

DATE :

DELTA ELECTRONICS, INC.

TAOYUAN PLANT

252, SHANG YING ROAD, GUIZHAN INDUSTRIAL ZONE

TAOYUAN CITY, TAIWAN, R.O.C.

TEL:886-(0)3-3591968

FAX:886-(0)3-3591991

Delta Electronics, Inc.
No.252, Shanying Rd., Guishan Dist.,
Taoyuan City 333, Taiwan (R.O.C.)

TEL : 886-(0)3-3591968
FAX : 886-(0)3-3591991

STATEMENT OF DEVIATION

NONE

DESCRIPTION:

Delta Electronics, Inc.
 No.252, Shanying Rd., Guishan Dist.,
 Taoyuan City 333, Taiwan (R.O.C.)

TEL : 886-(0)3-3591968
 FAX : 886-(0)3-3591991

Specification For Approval

Customer : DPC

Description : DC FAN

Customer P/N :

rev. :

Delta model no. : QFR1212GHEEVT

Delta Safety Model No.: QFR1212GHE

Sample revision. : 03

Issue no.:

Sample issue date : OCT.25 2019

Quantity :

1. SCOPE:

THIS SPECIFICATION DEFINES THE ELECTRICAL AND MECHANICAL CHARACTERISTICS OF THE DC BRUSHLESS AXIAL FLOW FAN.

2. CHARACTERS:

| ITEM | DESCRIPTION |
|--|--|
| RATED VOLTAGE | 12.0 VDC |
| OPERATION VOLTAGE | 10.8 - 12.6 VDC |
| INPUT CURRENT (AVG.) | 1.80 (MAX. 2.70) A (SAFETY CURRENT ON LABEL : 2.70A) |
| INPUT POWER (AVG.) | 21.60 (MAX. 32.40) W |
| SPEED | 6000 ±10% RPM |
| MAX. AIR FLOW (AT ZERO STATIC PRESSURE) | 5.957 (MIN. 5.361) M ³ /MIN. 210.38 (MIN. 189.34) CFM |
| MAX. AIR PRESSURE (AT ZERO AIRFLOW) | 29.179 (MIN. 23.635) mmH ₂ O 1.170 (MIN. 0.945) inchH ₂ O |
| ACOUSTICAL NOISE (AVG.) | 64.0 (MAX 68.0) dB-A |
| INSULATION TYPE | UL: CLASS A |
| INSULATION STRENGT | 10 MEG OHM MIN. AT 500 VDC (BETWEEN FRAME AND LEAD WIRES) |
| DIELECTRIC STRENGTH | 5mA MAX. AT 500 VAC 50/60 Hz ONE MINUTE.(BETWEEN FRAME AND LEAD WIRES.(USUALLY INSPECT AT 600V AC, 3SEC. 5mA.)) |

(continued)


PART NO:

DELTA MODEL: QFR1212GHEEVT

| | |
|--|--|
| LIFE EXPECTANCE(L10) (AT LABEL VOLTAGE) | 70,000 HOURS CONTINUOUS OPERATION AT 40 ° C WITH 15 ~ 65 %RH. |
| ROTATION | CLOCKWISE VIEW FROM LABEL PLATE SIDE |
| LOCKED ROTOR PROTECTION | THE CURRENT WILL SHUT DOWN WHEN ROTOR LOCKED AND FIXED. |
| STARTING PROTECTION | START AT LOW SPEED, AFTER 10 SEC RUNNING AT FULL SPEED. |

NOTES:

1. ALL READINGS ARE MEASURED AFTER STABLY WARMING UP THROUGH 10 MINUTES.
2. STANDARD AIR PROPERTY IS AIR AT (Td) 25°C TEMPERATURE, (RH) 65% RELATIVE HUMIDITY , AND (Pb) 760 mmHg BAROMETRIC PRESSURE.
3. THE VALUES WRITTEN IN PARENS , (), ARE LIMITED SPEC.
4. ACOUSTICAL NOISE MEASURING CONDITION:



NOISE IS MEASURED AT RATED VOLTAGE IN FREE AIR IN ANECHOIC CHAMBER WITH B & K SOUND LEVEL METER WITH MICROPHONE AT A DISTANCE OF ONE METER FROM THE FAN INTAKE.

PART NO:

DELTA MODEL: QFR1212GHEEVT

3. MECHANICAL:

- 3-1. DIMENSIONS----- SEE DIMENSIONS DRAWING
- 3-2. FRAME----- PLASTIC UL: 94V-0
- 3-3. IMPELLER----- PLASTIC UL: 94V-0
- 3-4. BEARING SYSTEM----- TWO BALL BEARINGS
- 3-5. WEIGHT----- 330 GRAMS (REF.)

4. ENVIRONMENTAL:

- 4-1. OPERATING TEMPERATURE----- -10 TO +60 DEGREE C
- 4-2. STORAGE TEMPERATURE----- -40 TO +70 DEGREE C
- 4-3. OPERATING HUMIDITY----- 5 TO 90 % RH
- 4-4. STORAGE HUMIDITY----- 5 TO 95 % RH

5. PROTECTION:

- 5-1. LOCKED ROTOR PROTECTION
IMPEDANCE OF MOTOR WINDING PROTECTS MOTOR FROM FIRE IN
96 HOURS OF LOCKED ROTOR CONDITION AT THE RATED VOLTAGE.
- 5-2. POLARITY PROTECTION
BE CAPABLE OF WITHSTANDING IF REVERSE CONNECTION FOR
POSITIVE AND NEGATIVE LEADS.

NOTE: TEST WITH PWM & FG/RD LEAD DISCONNECTED.

6. RE OZONE DEPLETING SUBSTANCES:

- 6-1. NO CONTAINING PBBs, PBBOs, CFCs, PBBEs, PBDPEs AND HCFCs.


7. PRODUCTION LOCATION

- 7-1. PRODUCTS WILL BE PRODUCED IN CHINA OR THAILAND.

PART NO:

DELTA MODEL: QFR1212GHEEVT

8. P & Q CURVE:





* TEST CONDITION: INPUT VOLTAGE ----- OPERATION VOLTAGE
TEMPERATURE ----- ROOM TEMPERATURE
HUMIDITY ----- 65%RH

PART NO:

DELTA MODEL: QFR1212GHEEVT

9.DIMENSION DRAWING:

LABEL:




NOTES:

1. HOUSING: MOLEX 22-01-3047 ----- 1PCE
2. TERMINAL: MOLEX 08-50-0113 ----- 4PCS
3. LEAD WIRES :
 - PIN1: BLACK WIRE -----(-)-----UL 1061 AWG#24
 - PIN2: RED WIRE -----(+)------UL 1061 AWG#24
 - PIN3: BLUE WIRE -----(F00)-----UL 1061 AWG#26
 - PIN4: YELLOW WIRE -----(PWM)-----UL 1061 AWG#26
4. THIS PRODUCT IS RoHS COMPLIANT

PART NO:

DELTA MODEL: QFR1212GHEEVT

10. FREQUENCY GENERATOR (FG) SIGNAL:
10-1 OUTPUT CIRCUIT - OPEN COLLECTOR MODE




CAUTION:

THE LEAD WIRE OF FG SIGNAL MUST BE KEPT AWAY FROM THE LEAD WIRE OF POSITIVE OR NEGATIVE.

10-2. SPECIFICATION:

$V_{FG} = 12.6V \text{ MAX.}$ $I_c = 5mA \text{ MAX.}$
 $V_{CE} = 0.5V \text{ MAX.}$ $R \geq V_{FG} / I_c$

10-3. ROTATION DETECT WAVEFORM:




$N = \text{RPM}$
 $T_S = 60/N(\text{SEC})$
*VOLTAGE LEVEL AFTER BLADE LOCKED
*4 POLES

PART NO:

DELTA MODEL: QFR1212GHEEVT

11. PWM CONTROL SIGNAL:

SIGNAL VOLTAGE RANGE: 0~15VDC




- * THE PREFERRED OPERATING POINT FOR THE FAN IS 25K HZ.
- * AT 100% DUTY CYCLE, THE ROTOR WILL SPIN AT MAXIMUM SPEED.
- * AT 0% DUTY CYCLE, THE ROTOR WILL SPIN AT MINIMUM SPEED.
- * WHEN CONTROL SIGNAL LEAD DISCONNECTED, THE FAN WILL SPIN AT MAXIMUM SPEED.
- * AT 25K HZ 0% DUTY CYCLE, THE FAN WILL BE ABLE TO START FROM A DEAD STOP.

12. SPEED VS PWM CONTROL SIGNAL:

(AT RATED VOLTAGE & PWM FREQUENCY=25KHz)

| DUTY CYCLE (%) | SPEED RPM (REF.) | CURRENT (A) TYP |
|----------------|------------------|-----------------|
| 100 | 6000 ± 10% | 1.80 |
| 0 | 700 ± 250 | 0.06 |

13. PWM CONTROL LEAD WIRE INPUT IMPEDANCE:



13-1. THE FAN SPEED WILL DEFAULT TO MAXIMUM WHEN THE SPEED CONTROL INPUT IS LEFT UNCONNECTED.



Application Notice

- 1. Delta will not guarantee the performance of the products if the application condition falls outside the parameters set forth in the specification.**
- 2. A written request should be submitted to Delta prior to approval if deviation from this specification is required.**
- 3. Please exercise caution when handling fans. Damage may be caused when pressure is applied to the impeller, if the fans are handled by the lead wires, or if the fan was hard-dropped to the production floor.**
- 4. Except as pertains to some special designs, there is no guarantee that the products will be free from any such safety problems or failures as caused by the introduction of powder, droplets of water or encroachment of insect into the hub.**
- 5. The above-mentioned conditions are representative of some unique examples and viewed as the first point of reference prior to all other information.**
- 6. It is very important to establish the correct polarity before connecting the fan to the power source. Positive (+) and Negative (-). Damage may be caused to the fans if connection is with reverse polarity, if there is no foolproof method to protect against such error specifically mentioned in this spec.**
- 7. Delta fans without special protection are not suitable where any corrosive fluids are introduced to their environment.**
- 8. Please ensure all fans are stored according to the storage temperature limits specified. Do not store fans in a high humidity environment. We highly recommend performance testing is conducted before shipping, if the fans have been stored over 6 months.**
- 9. Not all fans are provided with the Lock Rotor Protection feature. If you impair the rotation of the impeller for the fans that do not have this function, the performance of those fans will lead to failure.**
- 10. Please be cautious when mounting the fan. Incorrect mounting of fans may cause excess resonance, vibration and subsequent noise.**
- 11. It is important to consider safety when testing the fans. A suitable fan guard should be fitted to the fan to guard against any potential for personal injury.**
- 12. Except where specifically stated, all tests are carried out at room (ambient) temperature and relative humidity conditions of 25°C, 65% RH. The test value is only for fan performance itself.**
- 13. Be certain to connect an “ 4.7µF or greater” capacitor to the fan externally when the application calls for using multiple fans in parallel, to avoid any unstable power.**