



Power contactor, AC-3 7 A, 3 kW / 400 V 2 NO + 2 NC, 24 V DC with diode integrated 3-pole, Size S00 Screw terminal Captive auxiliary switch

|   |                                       |
|---|---------------------------------------|
| <b>product brand name</b>   | SIRIUS                                |
| <b>product designation</b>  | Power contactor                       |
| <b>product type designation</b>   | 3RT2                                  |
| <b>General technical data</b>   |                                       |
| <b>size of contactor</b>  | S00                                   |
| <b>product extension</b>  |                                       |
| <ul style="list-style-type: none"> <li>function module for communication</li> <li>auxiliary switch</li> </ul>   | No<br>No                              |
| <b>power loss [W] for rated value of the current</b>  |                                       |
| <ul style="list-style-type: none"> <li>at AC in hot operating state</li> <li>at AC in hot operating state per pole</li> <li>without load current share typical</li> </ul>   | 0.6 W<br>0.2 W<br>4 W                 |
| <b>insulation voltage</b>   |                                       |
| <ul style="list-style-type: none"> <li>of main circuit with degree of pollution 3 rated value</li> <li>of auxiliary circuit with degree of pollution 3 rated value</li> </ul>   | 690 V<br>690 V                        |
| <b>surge voltage resistance</b>   |                                       |
| <ul style="list-style-type: none"> <li>of main circuit rated value</li> <li>of auxiliary circuit rated value</li> </ul>   | 6 kV<br>6 kV                          |
| maximum permissible voltage for safe isolation between coil and main contacts according to EN 60947-1   | 400 V                                 |
| <b>shock resistance at rectangular impulse</b>  |                                       |
| <ul style="list-style-type: none"> <li>at DC</li> </ul>   | 6,7g / 5 ms, 4,2g / 10 ms             |
| <b>shock resistance with sine pulse</b>   |                                       |
| <ul style="list-style-type: none"> <li>at DC</li> </ul>   | 10,5g / 5 ms, 6,6g / 10 ms            |
| <b>mechanical service life (switching cycles)</b>   |                                       |
| <ul style="list-style-type: none"> <li>of contactor typical</li> <li>of the contactor with added electronically optimized auxiliary switch block typical</li> <li>of the contactor with added auxiliary switch block typical</li> </ul> | 10 000 000<br>5 000 000<br>10 000 000 |
| <b>reference code according to IEC 81346-2</b>  | Q                                     |
| <b>Substance Prohibitance (Date)</b>  | 10/01/2009                            |
| <b>Ambient conditions</b>   |                                       |
| installation altitude at height above sea level maximum   | 2 000 m                               |
| <b>ambient temperature</b>  |                                       |
| <ul style="list-style-type: none"> <li>during operation</li> <li>during storage</li> </ul>  | -25 ... +60 °C<br>-55 ... +80 °C      |
| <b>relative humidity minimum</b>  | 10 %                                  |
| <b>relative humidity at 55 °C according to IEC 60068-2-30 maximum</b>   | 95 %                                  |

## Main circuit

|  |                     |
|--|---------------------|
| <b>number of poles for main current circuit</b>                        | 3                   |
| <b>number of NO contacts for main contacts</b>                         | 3                   |
| <b>operating voltage</b>   |                     |
| • at AC-3 rated value maximum  | 690 V               |
| • at AC-3e rated value maximum   | 690 V               |
| <b>operational current</b>   |                     |
| • at AC-1 at 400 V at ambient temperature 40 °C rated value            | 18 A                |
| • at AC-1  |                     |
| — up to 690 V at ambient temperature 40 °C rated value                 | 18 A                |
| — up to 690 V at ambient temperature 60 °C rated value                 | 16 A                |
| • at AC-3  |                     |
| — at 400 V rated value   | 7 A                 |
| — at 500 V rated value   | 6 A                 |
| — at 690 V rated value   | 4.9 A               |
| • at AC-3e   |                     |
| — at 400 V rated value   | 7 A                 |
| — at 500 V rated value   | 6 A                 |
| — at 690 V rated value   | 4.9 A               |
| • at AC-4 at 400 V rated value   | 6.5 A               |
| • at AC-5a up to 690 V rated value                                     | 15.8 A              |
| • at AC-5b up to 400 V rated value                                     | 5.8 A               |
| • at AC-6a   |                     |
| — up to 230 V for current peak value n=20 rated value                  | 4 A                 |
| — up to 400 V for current peak value n=20 rated value                  | 4 A                 |
| — up to 500 V for current peak value n=20 rated value                  | 3.8 A               |
| — up to 690 V for current peak value n=20 rated value                  | 3.6 A               |
| • at AC-6a   |                     |
| — up to 230 V for current peak value n=30 rated value                  | 2.7 A               |
| — up to 400 V for current peak value n=30 rated value                  | 2.7 A               |
| — up to 500 V for current peak value n=30 rated value                  | 2.5 A               |
| — up to 690 V for current peak value n=30 rated value                  | 2.4 A               |
| minimum cross-section in main circuit at maximum AC-1 rated value      | 2.5 mm <sup>2</sup> |
| <b>operational current for approx. 200000 operating cycles at AC-4</b> |                     |
| • at 400 V rated value   | 2.6 A               |
| • at 690 V rated value   | 1.8 A               |
| <b>operational current</b>   |                     |
| • <b>at 1 current path at DC-1</b>                                     |                     |
| — at 24 V rated value  | 15 A                |
| — at 110 V rated value   | 1.5 A               |
| — at 220 V rated value   | 0.6 A               |
| — at 440 V rated value   | 0.42 A              |
| — at 600 V rated value   | 0.42 A              |
| • <b>with 2 current paths in series at DC-1</b>                        |                     |
| — at 24 V rated value  | 15 A                |
| — at 110 V rated value   | 8.4 A               |
| — at 220 V rated value   | 1.2 A               |
| — at 440 V rated value   | 0.6 A               |
| — at 600 V rated value   | 0.5 A               |
| • <b>with 3 current paths in series at DC-1</b>                        |                     |

|   |   |
|---|---|
| — at 24 V rated value   | 15 A  |
| — at 110 V rated value  | 15 A  |
| — at 220 V rated value  | 15 A  |
| — at 440 V rated value  | 0.9 A   |
| — at 600 V rated value  | 0.7 A   |
| ● <b>at 1 current path at DC-3 at DC-5</b>                              |   |
| — at 24 V rated value   | 15 A  |
| — at 110 V rated value  | 0.1 A   |
| ● <b>with 2 current paths in series at DC-3 at DC-5</b>                 |   |
| — at 24 V rated value   | 15 A  |
| — at 110 V rated value  | 0.25 A  |
| ● <b>with 3 current paths in series at DC-3 at DC-5</b>                 |   |
| — at 24 V rated value   | 15 A  |
| — at 110 V rated value  | 15 A  |
| — at 220 V rated value  | 1.2 A   |
| — at 440 V rated value  | 0.14 A  |
| — at 600 V rated value  | 0.14 A  |
| <b>operating power</b>  |   |
| ● at AC-2 at 400 V rated value  | 3 kW  |
| ● at AC-3   |   |
| — at 230 V rated value  | 1.5 kW  |
| — at 400 V rated value  | 3 kW  |
| — at 500 V rated value  | 3 kW  |
| — at 690 V rated value  | 4 kW  |
| ● at AC-3e  |   |
| — at 230 V rated value  | 1.5 kW  |
| — at 400 V rated value  | 3 kW  |
| — at 500 V rated value  | 3 kW  |
| — at 690 V rated value  | 4 kW  |
| <b>operating power for approx. 200000 operating cycles at AC-4</b>      |   |
| ● at 400 V rated value  | 1.15 kW   |
| ● at 690 V rated value  | 1.15 kW   |
| <b>operating apparent power at AC-6a</b>                                |   |
| ● up to 230 V for current peak value n=20 rated value                   | 1.5 kVA   |
| ● up to 400 V for current peak value n=20 rated value                   | 2.7 kVA   |
| ● up to 500 V for current peak value n=20 rated value                   | 3.3 kVA   |
| ● up to 690 V for current peak value n=20 rated value                   | 4.3 kVA   |
| <b>operating apparent power at AC-6a</b>                                |   |
| ● up to 230 V for current peak value n=30 rated value                   | 1 kVA   |
| ● up to 400 V for current peak value n=30 rated value                   | 1.8 kVA   |
| ● up to 500 V for current peak value n=30 rated value                   | 2.2 kVA   |
| ● up to 690 V for current peak value n=30 rated value                   | 2.9 kVA   |
| <b>short-time withstand current in cold operating state up to 40 °C</b> |   |
| ● limited to 1 s switching at zero current maximum                      | 120 A; Use minimum cross-section acc. to AC-1 rated value |
| ● limited to 5 s switching at zero current maximum                      | 86 A; Use minimum cross-section acc. to AC-1 rated value  |
| ● limited to 10 s switching at zero current maximum                     | 67 A; Use minimum cross-section acc. to AC-1 rated value  |
| ● limited to 30 s switching at zero current maximum                     | 52 A; Use minimum cross-section acc. to AC-1 rated value  |
| ● limited to 60 s switching at zero current maximum                     | 43 A; Use minimum cross-section acc. to AC-1 rated value  |
| <b>no-load switching frequency</b>                                      |   |
| ● at DC   | 10 000 1/h  |
| <b>operating frequency</b>  |   |
| ● at AC-1 maximum   | 1 000 1/h   |
| ● at AC-2 maximum   | 750 1/h   |
| ● at AC-3 maximum   | 750 1/h   |
| ● at AC-3e maximum  | 750 1/h   |
| ● at AC-4 maximum   | 250 1/h   |
| <b>Control circuit/ Control</b>   |   |
| <b>type of voltage of the control supply voltage</b>                    | DC  |

|   |   |
|---|---|
| <b>control supply voltage at DC</b>   |   |
| • rated value   | 24 V  |
| <b>operating range factor control supply voltage rated value of magnet coil at DC</b> |   |
| • initial value   | 0.8   |
| • full-scale value  | 1.1   |
| <b>design of the surge suppressor</b>   | diode   |
| <b>closing power of magnet coil at DC</b>   | 4 W   |
| <b>holding power of magnet coil at DC</b>   | 4 W   |
| <b>closing delay</b>  |   |
| • at DC   | 30 ... 100 ms                                   |
| <b>opening delay</b>  |   |
| • at DC   | 38 ... 65 ms                                    |
| <b>arcing time</b>  | 10 ... 15 ms                                    |
| <b>control version of the switch operating mechanism</b>                              | Standard A1 - A2                                |
| <b>Auxiliary circuit</b>  |   |
| number of NC contacts for auxiliary contacts<br>instantaneous contact                 | 2   |
| number of NO contacts for auxiliary contacts<br>instantaneous contact                 | 2   |
| operational current at AC-12 maximum  | 10 A  |
| <b>operational current at AC-15</b>   |   |
| • at 230 V rated value  | 6 A   |
| • at 400 V rated value  | 3 A   |
| • at 500 V rated value  | 2 A   |
| • at 690 V rated value  | 1 A   |
| <b>operational current at DC-12</b>   |   |
| • at 24 V rated value   | 10 A  |
| • at 48 V rated value   | 6 A   |
| • at 60 V rated value   | 6 A   |
| • at 110 V rated value  | 3 A   |
| • at 125 V rated value  | 2 A   |
| • at 220 V rated value  | 1 A   |
| • at 600 V rated value  | 0.15 A  |
| <b>operational current at DC-13</b>   |   |
| • at 24 V rated value   | 6 A   |
| • at 48 V rated value   | 2 A   |
| • at 60 V rated value   | 2 A   |
| • at 110 V rated value  | 1 A   |
| • at 125 V rated value  | 0.9 A   |
| • at 220 V rated value  | 0.3 A   |
| • at 600 V rated value  | 0.1 A   |
| <b>contact reliability of auxiliary contacts</b>                                      | 1 faulty switching per 100 million (17 V, 1 mA) |
| <b>UL/CSA ratings</b>   |   |
| <b>full-load current (FLA) for 3-phase AC motor</b>                                   |   |
| • at 480 V rated value  | 4.8 A   |
| • at 600 V rated value  | 6.1 A   |
| <b>yielded mechanical performance [hp]</b>  |   |
| • for single-phase AC motor   |   |
| — at 110/120 V rated value  | 0.25 hp   |
| — at 230 V rated value  | 0.75 hp   |
| • for 3-phase AC motor  |   |
| — at 200/208 V rated value  | 1.5 hp  |
| — at 220/230 V rated value  | 2 hp  |
| — at 460/480 V rated value  | 3 hp  |
| — at 575/600 V rated value  | 5 hp  |
| <b>contact rating of auxiliary contacts according to UL</b>                           | A600 / Q600                                     |
| <b>Short-circuit protection</b>   |   |
| <b>design of the fuse link</b>  |   |
| • for short-circuit protection of the main circuit                                    |   |

- with type of coordination 1 required
- with type of assignment 2 required

- for short-circuit protection of the auxiliary switch required

gG: 35A (690V,100kA), aM: 20A (690V,100kA), BS88: 35A (415V,80kA)  
 gG: 20A (690V,100kA), aM: 16A (690V, 100kA), BS88: 20A (415V, 80kA)  
 gG: 10 A (500 V, 1 kA)

#### Installation/ mounting/ dimensions

|  |  |
|--|--|
| <b>mounting position</b>   | +/-180° rotation possible on vertical mounting surface; can be tilted forward and backward by +/- 22.5° on vertical mounting surface |
| <b>fastening method</b>  | screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 60715   |
| <ul style="list-style-type: none"> <li>● side-by-side mounting</li> </ul>  | Yes  |
| <b>height</b>  | 58 mm  |
| <b>width</b>   | 45 mm  |
| <b>depth</b>   | 117 mm   |
| <b>required spacing</b>  |  |
| <ul style="list-style-type: none"> <li>● with side-by-side mounting           <ul style="list-style-type: none"> <li>— forwards 10 mm</li> <li>— upwards 10 mm</li> <li>— downwards 10 mm</li> <li>— at the side 0 mm</li> </ul> </li> <li>● for grounded parts           <ul style="list-style-type: none"> <li>— forwards 10 mm</li> <li>— upwards 10 mm</li> <li>— at the side 6 mm</li> <li>— downwards 10 mm</li> </ul> </li> <li>● for live parts           <ul style="list-style-type: none"> <li>— forwards 10 mm</li> <li>— upwards 10 mm</li> <li>— downwards 10 mm</li> <li>— at the side 6 mm</li> </ul> </li> </ul> |  |

#### Connections/ Terminals

|  |  |
|--|--|
| <b>type of electrical connection</b>   |  |
| <ul style="list-style-type: none"> <li>● for main current circuit</li> <li>● for auxiliary and control circuit</li> <li>● at contactor for auxiliary contacts</li> <li>● of magnet coil</li> </ul>   | screw-type terminals<br>screw-type terminals<br>Screw-type terminals<br>Screw-type terminals |
| <b>type of connectable conductor cross-sections</b>  |  |
| <ul style="list-style-type: none"> <li>● for main contacts           <ul style="list-style-type: none"> <li>— solid 2x (0.5 ... 1.5 mm<sup>2</sup>), 2x (0.75 ... 2.5 mm<sup>2</sup>), 2x 4 mm<sup>2</sup></li> <li>— solid or stranded 2x (0.5 ... 1.5 mm<sup>2</sup>), 2x (0.75 ... 2.5 mm<sup>2</sup>), 2x 4 mm<sup>2</sup></li> <li>— finely stranded with core end processing 2x (0.5 ... 1.5 mm<sup>2</sup>), 2x (0.75 ... 2.5 mm<sup>2</sup>)</li> </ul> </li> <li>● at AWG cables for main contacts 2x (20 ... 16), 2x (18 ... 14), 2x 12</li> </ul> |  |
| <b>connectable conductor cross-section for main contacts</b>   |  |
| <ul style="list-style-type: none"> <li>● solid 0.5 ... 4 mm<sup>2</sup></li> <li>● stranded 0.5 ... 4 mm<sup>2</sup></li> <li>● finely stranded with core end processing 0.5 ... 2.5 mm<sup>2</sup></li> </ul>   |  |
| <b>connectable conductor cross-section for auxiliary contacts</b>  |  |
| <ul style="list-style-type: none"> <li>● solid or stranded 0.5 ... 4 mm<sup>2</sup></li> <li>● finely stranded with core end processing 0.5 ... 2.5 mm<sup>2</sup></li> </ul>  |  |
| <b>type of connectable conductor cross-sections</b>  |  |
| <ul style="list-style-type: none"> <li>● for auxiliary contacts           <ul style="list-style-type: none"> <li>— solid or stranded 2x (0.5 ... 1.5 mm<sup>2</sup>), 2x (0.75 ... 2.5 mm<sup>2</sup>), 2x 4 mm<sup>2</sup></li> <li>— finely stranded with core end processing 2x (0.5 ... 1.5 mm<sup>2</sup>), 2x (0.75 ... 2.5 mm<sup>2</sup>)</li> </ul> </li> <li>● at AWG cables for auxiliary contacts 2x (20 ... 16), 2x (18 ... 14), 2x 12</li> </ul>   |  |
| <b>AWG number as coded connectable conductor cross section</b>   |  |
| <ul style="list-style-type: none"> <li>● for main contacts 20 ... 12</li> <li>● for auxiliary contacts 20 ... 12</li> </ul>  |  |

#### Safety related data

|   |  |
|---|--|
| <b>product function</b>   |  |
| <ul style="list-style-type: none"> <li>• mirror contact according to IEC 60947-4-1</li> <li>• positively driven operation according to IEC 60947-5-1</li> </ul> | Yes<br>No  |
| B10 value with high demand rate according to SN 31920   | 1 000 000  |
| <b>proportion of dangerous failures</b>   |  |
| <ul style="list-style-type: none"> <li>• with low demand rate according to SN 31920</li> <li>• with high demand rate according to SN 31920</li> </ul>           | 40 %<br>73 %                                     |
| failure rate [FIT] with low demand rate according to SN 31920   | 100 FIT  |
| T1 value for proof test interval or service life according to IEC 61508   | 20 y   |
| <b>protection class IP on the front according to IEC 60529</b>  | IP20   |
| <b>touch protection on the front according to IEC 60529</b>   | finger-safe, for vertical contact from the front |
| <b>suitability for use</b>  |  |
| <ul style="list-style-type: none"> <li>• safety-related switching OFF</li> </ul>  | Yes  |

#### Certificates/ approvals

##### General Product Approval



[Confirmation](#)



[KC](#)



|     |                                       |                           |                   |
|-----|---------------------------------------|---------------------------|-------------------|
| EMC | Functional Safety/Safety of Machinery | Declaration of Conformity | Test Certificates |
|-----|---------------------------------------|---------------------------|-------------------|



[Type Examination Certificate](#)



EG-Konf.



[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)

#### Marine / Shipping



|                   |       |                |
|-------------------|-------|----------------|
| Marine / Shipping | other | Dangerous Good |
|-------------------|-------|----------------|



[Confirmation](#)



[Transport Information](#)

#### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT2015-1FB44-3MA0>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT2015-1FB44-3MA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2015-1FB44-3MA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RT2015-1FB44-3MA0&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2015-1FB44-3MA0&lang=en)

Characteristic: Tripping characteristics, I<sub>t</sub>, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2015-1FB44-3MA0/char>

**Further characteristics (e.g. electrical endurance, switching frequency)**

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mfb=3RT2015-1FB44-3MA0&objecttype=14&gridview=view1>

last modified:

6/2/2022 