



NOTES: Finish (Plating Thickness in Micro-inches)
 1. Brass
 2. Albaloy Plating (Copper-Tin-Zinc) Pl. 80 Min, Thick
 3. Phosphor Bronze
 4. Gold Pl. 5 Min Thick over Copper Pl. 50 Min. Thick
 5. Teflon
 6. Passivated

RoHS Compliant

| | | | | | | | | | |
|---------------------------------------|-------------|----------|--------|----------|-------------|--------------------------|------------------------|-------|---|
| Dimensions are in Inches | | | | Part No. | | <h1>NTE Electronics</h1> | | | |
| Unless Otherwise Specified Tolerances | | | | Approved | Date | | Title | | |
| 0.5-6 = ±0.2 | | | | | 12-21-2018 | | N Plug to Jack Adapter | | |
| 6-30 = ±0.4 | | | | Checked | Date | | Drawing No. | | |
| 30-120 = ±0.6 | | | | | 12-21-2018 | 06-N015 | | | |
| 120-315 = ±1 | | | | Drawn | Date | File No. | | | |
| 315-1000 = ±1.6 | | | | | 12-21-2018 | | | | |
| 1000-2000 = ±2.4 | | | | | | | | | |
| No. | Description | Material | Finish | Q'ty | Drawing No. | Scale | 3/1 | Issue | A |

| | | | | | |
|---|---------------|----------|---------|---|--|
| 7 | Shell | Note 1 | Note 2 | 1 | |
| 6 | Gasket | Silicone | Red | 1 | |
| 5 | Retainer Ring | SUS 304 | Note 6 | 1 | |
| 4 | Contact Body | Note 1 | Note 2 | 1 | |
| 3 | Contact Pin | Note 3 | Note 4 | 1 | |
| 2 | Insulator | Note 5 | Natural | 1 | |
| 1 | Body | Note 1 | Note 2 | 1 | |