

SPEED2 LE 2 Port PCI Serial Card

 perle.com/products/pci-serial-port-cards/speed2le-dual-port-serial-card.shtml

RS232 Serial Cards

- 2 x DB9M
- Universal 3.3v/5v PCI bus slot support (PCI 2.3 compliant)
- PCI-X compatible
- Low profile card with standard bracket and low profile bracket included
- 16550 UART for software compatibility
- 921.6Kbps bi-directional serial communication speeds
- 15 kV electrostatic discharge protection
- Full modem control and hardware/software flow control

Availability: **in stock**

Part Number: 04003060



[Buy Now](#) [Volume Pricing](#)

Supported Operating System Drivers

- Windows® Server 2016
- Windows® 10
- Windows® Server 2012 R2
- Windows® 8.1 (32 / 64 Bit)
- Windows® Server 2012
- Windows® 8 (32 / 64 Bit)
- Windows® Server 2008 R2
- Windows® 7 (32 / 64 Bit)
- Windows® Server 2008 (32 / 64 Bit)
- Windows® Vista (32 / 64 Bit)
- Windows® Server 2003 (32 / 64 Bit)
- Windows® XP (32 / 64 Bit)
- Windows® 2000
- Linux 3.x, 2.6.x, 2.4.x, 2.2.16+ (32 / 64 Bit)

For Solaris x86, Solaris SPARC, SCO OpenServer and SCO UnixWare, we recommend [UltraPort Serial Cards](#).

Connectors

2x DB9M

Serial Port Protection

15Kv Electrostatic Discharge Protection (ESD)

Signal support

TXD, RXD, RTS, CTS, DTR, DCD, DSR, RI

UART

16C950 (16C550 compatible)

Environmental

Reach, RoHS and WEEE Compliant

Approvals



- FCC Part15 ,Class B
- EN55022:1998 + A1:2000 + A2:2003 Class A
- EN55024:1998 + A1:2001 + A2:2003
- EN60950-1:2001 +A11:2004

Form Factor

SPEED2 LE are low profile MD1 cards shipped with standard sized brackets. Low profile brackets are included

Warranty: Limited Lifetime Warranty

HSTUS Number: 8517.62.0050

ECCN Number: 5A991

Copyright © 1996 - 2021 Perle. All Rights Reserved