

## Surge protection device - TT-UK-R-F/250AC - 2788249

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Modular double terminal block with gas-filled surge arrester as coarse protection between both levels, nominal voltage: 250 V AC, for mounting on NS 32 or NS 35/7.5, closed housing, terminal width: 15.5 mm, terminal height: 45.5 mm



### Key commercial data

Packing unit	1 pc
GTIN	 4 017918 071455
Weight per Piece (excluding packing)	30.16 GRM
Custom tariff number	85363010
Country of origin	Greece

### Technical data

#### Dimensions

Height	45.5 mm
Width	15.3 mm
Length	50 mm

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 80 °C
Degree of protection	IP20

#### General

Housing material	PA
Inflammability class according to UL 94	V2
Color	black
Standards for air and creepage distances	VDE 0110-1
Mounting type	DIN rail/G-profile rail

## Surge protection device - TT-UK-R-F/250AC - 2788249

### Technical data

#### General

Type	Single-level terminal block – two-channel
Direction of action	Line-Line

#### Protective circuit

IEC test classification	C2
	D1
VDE requirement class	C2
	D1
Nominal voltage $U_N$	250 V AC
Maximum continuous operating voltage $U_C$	150 V DC
	250 V AC
Maximum continuous voltage $U_C$ (wire-wire)	150 V DC
	250 V AC
Nominal current $I_N$	2 A
Operating effective current $I_C$ at $U_C$	$\leq 2 \mu A$
Residual current $I_{PE}$	$\leq 2 \mu A$
Nominal discharge current $I_n$ (8/20) $\mu s$ (Core-Core)	20 kA
Total surge current (8/20) $\mu s$	20 kA
Max. discharge current $I_{max}$ (8/20) $\mu s$ maximum (Core-Core)	20 kA
Output voltage limitation at 1 kV/ $\mu s$ (Core-Core) spike	$\leq 1.4$ kV
Response time $t_A$ (Core-Core)	$\leq 100$ ns
Capacity (Core-Core)	$\leq 1.5$ pF
Surge carrying capacity in acc. with IEC 61643-21 (Core-Core)	C2 - 10 kV / 5 kA
	D1 (20 kV/2.5 kA)
Alternating current carrying capacity in acc. with IEC 61643-21 (Core-Earth)	20 A (1 s)

#### Connection data

Connection method	Screw connection
Connection type IN	Screw terminal blocks
Connection type OUT	Screw terminal blocks
Screw thread	M3
Tightening torque	0.5 Nm
Stripping length	8 mm
Conductor cross section stranded min.	0.2 mm <sup>2</sup>
Conductor cross section stranded max.	2.5 mm <sup>2</sup>
Conductor cross section solid min.	0.2 mm <sup>2</sup>
Conductor cross section solid max.	4 mm <sup>2</sup>

## Surge protection device - TT-UK-R-F/250AC - 2788249

### Technical data

#### Connection data

Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12

#### Standards and Regulations

Standards/regulations	IEC 61643-21
-----------------------	--------------

### Classifications

#### eCl@ss

eCl@ss 4.0	27140201
eCl@ss 4.1	27130801
eCl@ss 5.0	27130801
eCl@ss 5.1	27130801
eCl@ss 6.0	27130807
eCl@ss 7.0	27130807
eCl@ss 8.0	27130807

#### ETIM

ETIM 2.0	EC000943
ETIM 3.0	EC000943
ETIM 4.0	EC000943
ETIM 5.0	EC000943

#### UNSPSC

UNSPSC 6.01	30212010
UNSPSC 7.0901	39121610
UNSPSC 11	39121610
UNSPSC 12.01	39121610
UNSPSC 13.2	39121620

### Approvals

#### Approvals

---

Approvals

GOST / GOST

---

## Surge protection device - TT-UK-R-F/250AC - 2788249

### Approvals

Ex Approvals

---

Approvals submitted

---

### Approval details


GOST 

GOST 


### Drawings

# Surge protection device - TT-UK-R-F/250AC - 2788249

Schematic diagram



Circuit diagram



## Surge protection device - TT-UK-R-F/250AC - 2788249

Schematic diagram

