

1

2

3

4

5

6

7

A

A

④

③

②

With Liquid Glue

①

B

B

C

C

⑤

D

D

Note:

\* ⓐ Important Dimension.

\* Waterproof Rate: IP66

\* Connector: Black, Nylon+GF

\* Pin: Copper Alloy, Gold Plated

\* Seals B1 for Cable OD:  $\phi 4.5\text{mm} \sim \phi 6.5\text{mm}$ \* Seals B2 for Cable OD:  $\phi 3.5\text{mm} \sim \phi 5.3\text{mm}$ 

\* One Set Unassembled in One PE Bag

E

E

Pin Assignments  
Front View

F

F

**RoHS compliant**


Unit: mm

G

G

H

H

Scale	Free				Date	Name	Customer-No.
TOLERANCE					Drawn	09.06.2014	Joanna
Unit	±XX				Approved	09.06.2014	Joanna
.X	±0.25						ASSMANN WSW-No. A-CR-03BMMA-L180-WP
.XX	±0.1						Drawing-No.
.XXX	±0.05						ASS 6366 CO
DIM	Tol						rev00
		ⓐ	Drawn	09.06.2014	Joanna		
Angle	±1°	Id.	Modification	Date	Name		

1

2

3

4

5

6

7