## 9002AW1

Foot Switch, Harmony, industrial, unshielded, 5A resistive at 600 VAC, SPDT contact, NEMA 2, 4, 13 enclosure



# Main

Main	
Range	9002AW
Product	Foot switch
Contact Operation	1 step
Certifications	CSA UL Listed
Cable Entry	0.75 inch NPT conduit entrance
Contact Arrangement	SPDT
Enclosure Rating	NEMA 2/4/13
Voltage Rating	600 V AC/DC
Protection	Unshielded
Operator Action	Spring return
Rated Breaking Capacity	15 A 120 V AC inductive control circuit UL 508 10 A 240 V AC inductive control circuit UL 508 6 A 480 V AC inductive control circuit UL 508 5 A 600 V AC inductive control circuit UL 508 15 A 120 V AC resistive control circuit UL 508 0.5 A 125 V DC resistive control circuit UL 508
Height	3.90 in (99 mm)
Width	4.49 in (114 mm)
Depth	8.50 in (216 mm)

#### Ordering and shipping details

Ordering and shipping details		
Category	21441 - 9002 AW FOOT SWITCHES	_
Discount Schedule	CS1	
GTIN	785901815433	
Nbr. of units in pkg.	1	
Package weight(Lbs)	3.11 lb(US) (1.411 kg)	
Returnability	Yes	
Country of origin	MX	

#### **Packing Units**

Unit Type of Package 1	PCE	
Package 1 Height	3.50 in (8.89 cm)	
Package 1 width	5.00 in (12.7 cm)	
Package 1 Length	9.00 in (22.86 cm)	

### Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS  Declaration	
Mercury free	Yes	

RoHS exemption information	₫Yes	
China RoHS Regulation	<sup>™</sup> China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
Contractual warranty		

18 months

Warranty