24 INCHES LENGTH

Connector A 132119 SMA Jack Straight Bulkhead - Rear Mount Brass Gold + Heatshrink 50 Ohm RG-174 Continuity/Hi-Pot Connector B 3FA1ENZRJ-C01Y3 FAKRA Jack Right Angle Zinc Nickel + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

Right Angle	Connector A			Cable			Connector B		
90° 135° 180° 225° 270° 270° D-Flat Bulkhead	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting:	132119	6174 RG188 RG316 500 Mount	Part #: Description: Dielectric: Shielding: Diameter: Impedance: Sheathing: Testing: Length:	RG-174 RG-174 - PE 0.1 PE Braid 0.1 50 Ohm None Continuity Hi-Pot 24 Inches	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting: Clocking:	3FA1ENZRJ-C01Y3 FAKRA-Z JK RA R0 FAKRA Jack Right Angle Crimp Standard 50 Ohm Cable Zinc Nickel None Beryllium Copper Gold 3 GHz FAKRA-Z Jack Righ 0°	G174 RG316 50O	
Amphenol CUSTOM CABLE CONTROLLED DOCLUMENT DO NOT CODY			THIS DRAWING MAY CONTAIN PROPRIETARY INFORMATION FOR ANY PURPOSE DETRIMEN INC. IT MAY NOT BE REPRODU IN ANY FORM WITHOUT THE CUSTOM CABLE INC. ACCEPT. ESTABLISHES AND AGREEME	AND MUST NOT BE U TAL TO CUSTOM CA JCED OR TRANSCRIB WRITTEN CONSENT O ANCE OF THIS DRAW	BLE ED F ING Part No:	art No:		UNLESS SPECIFIED TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES	