




US6-XX-XX-F-KIT

Ruland US6-XX-XX-F-KIT, Machinable Bore Single Universal Joint Kit, Friction Bearing, Steel, 0.370" (9.4mm) OD, 1.750" (44.5mm) Length





Description

Ruland US6-XX-XX-F-KIT is a single cardan friction bearing universal joint kit that can be machined with a bore size and geometry of the user's choice. It has a 0.370" (9.4mm) OD and 1.750" (44.5mm) length. US6-XX-XX-F-KIT is ideal for applications with space constraints and has higher torque capacity than equivalently sized double universal joints. This plain bearing universal joint is comprised of pins and blocks that are precision machined, selectively heat treated, and ground for high strength, accuracy, and wear resistance. The combination of these components with precision ground and hardened yoke ears allow for a longer lifespan, increased performance in demanding applications, and greater angular misalignment of up to 45° when compared to commodity style single universal joints. US6-XX-XX-F-KIT is made from high grade alloy steel for durability and high strength. It can be combined with boot UBOOT6/10-NI-KIT to protect the joint from unwanted contaminants such as dust or water and self lubricate reducing maintenance time. This single cardan universal joint is manufactured in the USA by Belden Universal for strict control of processes.

Product Specifications

1 Max Shaft Penetration 0.670 in (17.0 mm) B2 Max Shaft Penetration 0.670 in (17.0 mm) oint Outer Diameter (OD) 0.370 in (9.4 mm) Length (L) 1.750 in (44.5 mm) oke Length (LY) 0.875 in (22.2 mm) Hub Depth (LH) 0.670 in (17.0 mm) ax Round Bore (Inch) 0.2188 in Max Round Bore (Metric) 5 mm ax Hex or Square Bore (Inch) 0.1875 in Max Hex or Square Bore (Metric) 5 mm ax Blind Bore (Inch) 0.2500 in Max Blind Bore (Metric) 6 mm ax Operating Angle 45° Material Specification Alloy Steel anufacturer Belden Universal Country of Origin USA Veight (Ibs) 0.046000 Recommended Lubricant LUBRIPLATE No. 1200-2 atching Boot Cover UBOOT6/10-NI-KIT UPC 634529290194 ariff Code 8483.60.4000 UNSPC 25173810 Performance ratings are for guidance only. The user must determine suitability for a particular application of the control o				
bint Outer Diameter (OD) 0.370 in (9.4 mm) Length (L) 1.750 in (44.5 mm) 0.875 in (22.2 mm) Hub Depth (LH) 0.670 in (17.0 mm) ax Round Bore (Inch) 0.2188 in Max Round Bore (Metric) 5 mm ax Hex or Square Bore (Inch) 0.1875 in Max Hex or Square Bore (Metric) 5 mm ax Blind Bore (Inch) 0.2500 in Max Blind Bore (Metric) 6 mm eak Torque 100 in-lb (11.3 Nm) Rated Torque 20 in-lb (2.3 Nm) ax Operating Angle 45° Material Specification Alloy Steel anufacturer Belden Universal Country of Origin USA leight (Ibs) 0.046000 Recommended Lubricant LUBRIPLATE No. 1200-2 atching Boot Cover UBOOT6/10-NI-KIT UPC 634529290194 ariff Code 8483.60.4000 UNSPC 25173810 Performance ratings are for guidance only. The user must determine suitability for a particular application of the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	Bore (B1)	No Bore	Small Bore (B2)	No Bore
oke Length (LY) 0.875 in (22.2 mm) Hub Depth (LH) 0.670 in (17.0 mm) ax Round Bore (Inch) 0.2188 in Max Round Bore (Metric) 5 mm ax Hex or Square Bore (Inch) 0.1875 in Max Hex or Square Bore (Metric) 5 mm ax Blind Bore (Inch) 0.2500 in Max Blind Bore (Metric) 6 mm eak Torque 100 in-lb (11.3 Nm) Rated Torque 20 in-lb (2.3 Nm) ax Operating Angle 45° Material Specification Alloy Steel anufacturer Belden Universal Country of Origin USA reight (Ibs) 0.046000 Recommended Lubricant LUBRIPLATE No. 1200-2 atching Boot Cover UBOOT6/10-NI-KIT UPC 634529290194 ariff Code 8483.60.4000 UNSPC 25173810 Performance ratings are for guidance only. The user must determine suitability for a particular application of the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	B1 Max Shaft Penetration	0.670 in (17.0 mm)	B2 Max Shaft Penetration	0.670 in (17.0 mm)
ax Round Bore (Inch) ax Hex or Square Bore (Inch) ax Blind Bore (Metric) 6 mm Beak Torque 100 in-lb (11.3 Nm) Attend Torque 20 in-lb (2.3 Nm) Alloy Steel Alloy Steel Alloy Steel Alloy Steel Alloy Steel Belden Universal Country of Origin USA Beight (Ibs) 0.046000 Recommended Lubricant LUBRIPLATE No. 1200-2 Atching Boot Cover Atching Boot Cover UBOOT6/10-NI-KIT UPC 634529290194 Attended Bore (Metric) 5 mm Max Hex or Square Bore (Metric) 5 mm Alloy Steel Country of Origin USA Belden Universal UPSA UNSPC 25173810 Ote 1 Performance ratings are for guidance only. The user must determine suitability for a particular application of the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	Joint Outer Diameter (OD)	0.370 in (9.4 mm)	Length (L)	1.750 in (44.5 mm)
ax Hex or Square Bore (Inch) 0.1875 in Max Hex or Square Bore (Metric) 6 mm eak Torque 100 in-lb (11.3 Nm) Rated Torque 20 in-lb (2.3 Nm) ax Operating Angle 45° Material Specification Alloy Steel anufacturer Belden Universal Country of Origin USA Veight (Ibs) 0.046000 Recommended Lubricant LUBRIPLATE No. 1200-2 atching Boot Cover UBOOT6/10-NI-KIT UPC 634529290194 ariff Code 8483.60.4000 UNSPC 25173810 Performance ratings are for guidance only. The user must determine suitability for a particular application of the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	Yoke Length (LY)	0.875 in (22.2 mm)	Hub Depth (LH)	0.670 in (17.0 mm)
ax Blind Bore (Inch) eak Torque 100 in-lb (11.3 Nm) Rated Torque 20 in-lb (2.3 Nm) ax Operating Angle 45° Material Specification Alloy Steel anufacturer Belden Universal Country of Origin USA Veight (Ibs) 0.046000 Recommended Lubricant LUBRIPLATE No. 1200-2 atching Boot Cover UBOOT6/10-NI-KIT UPC 634529290194 arriff Code 8483.60.4000 UNSPC 25173810 ote 1 Performance ratings are for guidance only. The user must determine suitability for a particular application of the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	Max Round Bore (Inch)	0.2188 in	Max Round Bore (Metric)	5 mm
eak Torque 100 in-lb (11.3 Nm) Rated Torque 20 in-lb (2.3 Nm) Alloy Steel Alloy Steel Country of Origin USA Ceight (Ibs) 0.046000 Recommended Lubricant UBRIPLATE No. 1200-2 Ceight Gode Country Gode Country of Origin USA Cubricant UBRIPLATE No. 1200-2 Country of Origin USA Country of Origin USA Cubricant UBRIPLATE No. 1200-2 Country of Origin USA Country of Origin USA Country of Origin USA Cubricant Country of Origin USA Country of Origin USA Cubricant Cubricant Country of Origin USA Cubricant Country of Origin USA Country of Origin USA Cubricant Country of Origin USA Country of Origin USA Country of Origin USA Cubricant Country of Origin USA Cou	Max Hex or Square Bore (Inch)	0.1875 in	Max Hex or Square Bore (Metric)	5 mm
ax Operating Angle anufacturer Belden Universal Country of Origin USA Veight (Ibs) 0.046000 Recommended Lubricant UBRIPLATE No. 1200-2 Very atching Boot Cover UBOOT6/10-NI-KIT UPC 634529290194 Very ariff Code Very 48483.60.4000 VINSPC 25173810 Very 49483.60.4000 VINSPC Very 4959290194 Very 4979290194 Ver	Max Blind Bore (Inch)	0.2500 in	Max Blind Bore (Metric)	6 mm
anufacturer Belden Universal Country of Origin USA Veight (Ibs) 0.046000 Recommended Lubricant LUBRIPLATE No. 1200-2 atching Boot Cover UBOOT6/10-NI-KIT UPC 634529290194 ariff Code 8483.60.4000 UNSPC 25173810 ote 1 Performance ratings are for guidance only. The user must determine suitability for a particular application of the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	Peak Torque	100 in-lb (11.3 Nm)	Rated Torque	20 in-lb (2.3 Nm)
Veight (lbs) 0.046000 Recommended Lubricant LUBRIPLATE No. 1200-2 atching Boot Cover UBOOT6/10-NI-KIT UPC 634529290194 arriff Code 8483.60.4000 UNSPC 25173810 ote 1 Performance ratings are for guidance only. The user must determine suitability for a particular application of the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	Max Operating Angle	45°	Material Specification	Alloy Steel
atching Boot Cover UBOOT6/10-NI-KIT UPC 634529290194 8483.60.4000 UNSPC 25173810 Ote 1 Performance ratings are for guidance only. The user must determine suitability for a particular application of the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	Manufacturer	Belden Universal	Country of Origin	USA
ariff Code 8483.60.4000 UNSPC 25173810 Ote 1 Performance ratings are for guidance only. The user must determine suitability for a particular application of the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	Weight (lbs)	0.046000	Recommended Lubricant	LUBRIPLATE No. 1200-2
ote 1 Performance ratings are for guidance only. The user must determine suitability for a particular applica rop 65 ▲ WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	Matching Boot Cover	UBOOT6/10-NI-KIT	UPC	634529290194
rop 65 WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to	Tariff Code	8483.60.4000	UNSPC	25173810
California to cause cancer and birth defects or other reproductive harm. For more information go to	Note 1	Performance ratings are for guidance only. The user must determine suitability for a particular application.		
	Prop 65	·		