



General ordering data

Order No.	9510280000
Part designation	Klippon POK 8 Ex
Version	EXI enclosure, 120 mm, 250 mm, 255 mm, glass fibre-reinforced polyester
EAN	4008190498641
Qty.	1 pc(s).

Dimensions

Fixing dimension, height	200 mm
Fixing dimension, width	235 mm
Height	120 mm
Length	250 mm
Width	255 mm

General details

Cover fixing	4 stainless steel M6 screws
Enclosure fixing	Holes 6 mm
Sealing material	Polyurethane and chloroprene
Colour	grey
Class of protection to EN 60529	IP 66
Weight	2,650 g
Ambient temperature, min.	-40 °C
Ambient temperature, max.	90 °C

Screwed cable glands top/bottom

M 12	36
M 16	32
M 20	18
M 25	10
M 32	8
M 40	3
M 50	2
Side of enclosure	Top / Bottom

Screwed cable glands, left/right

M12	32
M16	21
M20	15
M25	8
M32	3
M40	3
M50	2
On housing side	left / right

Approvals

Approvals institutes



Classifications

ETIM 2.0	EC000520
ETIM 3.0	EC000049
eClass 4.1	27-14-12-06
eClass 5.0	27-18-05-02
eClass 5.1	27-18-05-02

Similar products

Order No.	Part designation	Version
1565420000	Klippon POK 8	Housings, 120 mm, 250 mm, 255 mm, glass fibre-reinforced polyester