

45° VERSA BAR

SPECIFICATION:

Input Voltage	12VDC or 24VDC
CRI	80+
Dimmable	0-10V, ELV, MLV
Color Temp	<div style="display: flex; gap: 10px;"> <div style="width: 15px; height: 15px; background-color: #f9c796; border: 1px solid black;"></div> 3000K <div style="width: 15px; height: 15px; background-color: #a2c4c9; border: 1px solid black;"></div> 4000K <div style="width: 15px; height: 15px; background-color: #74a9d4; border: 1px solid black;"></div> 6250K </div>
Max Run	4.9 ft/driver
IP Rating	IP50 - damp locations
Mounting	Screws and mounting clips included
Connectors	All 45° Versa Bars have a mini female barrel connector on both ends.
Dimensions	W 1.3" (33mm) x H 0.73" (8.2mm)
Finish	Silver
Lens	Frosted or Clear
Warranty	1 year limited



Accessories included:

Screws, mounting clips, 45° Versa-to-45° Versa connector, and 6" 45° Versa-to-standard female barrel connector

Certifications:



WATTAGE & LIGHT OUTPUT:

LENGTH	WATTAGE	WW LUMEN OUTPUT		NW LUMEN OUTPUT		CW LUMEN OUTPUT	
		Clear	Frosted	Clear	Frosted	Clear	Frosted
12in	3W	250 lm	200 lm	250 lm	200 lm	250 lm	200 lm
20in	5W	420 lm	350 lm	420 lm	350 lm	420 lm	350 lm
40in	11W	820 lm	720 lm	820 lm	720 lm	820 lm	720 lm

PART NUMBER BUILDER / ORDERING GUIDE

Example part number: V2F45D20WW12V

