TE Internal #: 1587826-3

Cable Seal, Silicone, Green, 4.9 mm [.192 in] Cavity Diameter, -40 –

125 °C [-40 – 257 °F] Operating Temperature

View on TE.com >



Connectors > Connector Accessories > Connector Seals & Cavity Plugs



Connector Seal & Plug Type: Cable Seal

Primary Product Material: Silicone
Primary Product Color: Green
Cavity Diameter: 4.9 mm [.192 in]
Resistance to Hydrocarbons: Poor

Features

Product Type Features

| Connector Seal & Plug Type | Cable Seal |
|-----------------------------|----------------------------|
| Body Features | |
| Primary Product Material | Silicone |
| Primary Product Color | Green |
| Housing Features | |
| Centerline (Pitch) | 10.4 mm[.409 in] |
| Dimensions | |
| Cavity Diameter | 4.9 mm[.192 in] |
| Usage Conditions | |
| Operating Temperature (Max) | 125 °C[257 °F] |
| Operating Temperature Range | -40 – 125 °C[-40 – 257 °F] |
| Packaging Features | |
| Packaging Quantity | 500 |
| Packaging Method | Box |
| Other | |
| Resistance to Hydrocarbons | Poor |
| | |

Yes

Product Compliance

Contains Lubricant



For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant |
|---|---|
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC |
| Halogen Content | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free |
| Solder Process Capability | Not reviewed for solder process capability |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Customers Also Bought





TE Part #1587827-3

CABLE SEAL RETAINER, SIZE C,
HVA280-2PI



TE Part #1-2325010-1 3POS,8MM HV,REC HSG,90 DEG, ASSY,SLD



TE Part #2302636-1
INSULATION INSERT,180DEG,UL94V-0





TE Part #2319655-3 SHIELDING SLEEVE,180DEG



TE Part #2328073-2 HV 8MM; DEEP DRAWN SOCKET 90 DEG. ASSEMB

TE Part #2310469-1 CABLE SEAL RTNR, SIZE B, HVA280-2PI, VO TE Part #2310469-2 CABLE SEAL RTNR, SIZE C, HVA280-2PI, V0

TE Part #2310537-4
PLUG ASSY, KEY D, CPA, HVA280-2PHI, V0

TE Part #2356073-2 SWS,HVP800,CVTY DIA,12.5,NAT, 8MM,HV

Documents

Product Drawings

CABLE SEAL, SIZE C, HVA280-2PI

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1587826-3_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1587826-3_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1587826-3_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Cable Seal, Silicone, Green, 4.9 mm [.192 in] Cavity Diameter, -40 - 125 °C [-40 - 257 °F] Operating Temperature



Application Specification

English