MICRO SWITCH
A DIVISION OF MINNEAPOLIS-HONEYWELL REGULATOR COMPANY
FREEPORT, ILLINOIS

FED. MFR. CODE 91929

SWITCH-ENCLOSED

102ML1-E1

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.



NOTE —

1. LISTED BY UNDERWRITERS LABORATORY, INC. FOR USE IN CLASS I GROUPS C AND D VAPOR-AIR ATMOSPHERES, AND CLASS 2 GROUPS E, F AND G DUST-AIR ATMOSPHERES
2. IT IS ESSENTIAL THAT THE CONDUIT OPENING BE PROPERLY SEALED IN ORDER TO MAINTAIN THE EXPLOSION PROOF PROPERTIES.
3. SWITCH WILL PERFORM SATISFACTORILY IN TEMPERATURES TO MINUS 30°F.

CHARACTERISTICS (TENTATIVE)

OPERATING FORCE	6 LB. APPROX.
RELEASE FORCE	4 LB. APPROX.
DIFFERENTIAL TRAVEL	.020 MAX.
OVERTRAVEL	.500 MIN.
SWITCH-BASIC REPLACEMENT	1MN1

ELECTRICAL DATA

CONTACT ARRANGEMENT
TWO CIRCUIT DOUBLE THROW
DOUBLE BREAK

(A) 10 A-120, 240, OR 480 VAC, 1/2 HP-120 VAC
1 HP-240 VAC; 0.8 A-115 VDC; 0.4 A-230 VDC
(B) PILOT DUTY: 720 VA-HEAVY DUTY
600 VAC MAX
(C)

UL
CSA

SCALE 1/2 TO 1
DO NOT SCALE PRINT

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCES ARE:

ONE PLACE	(.0)	±.030
TWO PLACE	(.00)	±.018
THREE PLACE	(.000)	±.008
ANGLES		±

WEIGHT

REPLACES
RELEASE NO. SR 7257
8 FEB. 58 EWL
7 FEB. 58 JNM
14 FEB. 58 GCH
5 FEB. 58
R. E. R. DRAWN CHECK