


Super Fast Recovery Rectifier




Features

- Ultrafast reverse recovery time
- Low leakage current
- Low switching losses, high efficiency
- High forward surge capability
- Glass passivated chip junction
- Solder dip 275 °C max. 7 s, per JESD 22-B106

Typical Applications

For use in high frequency rectification and freewheeling application in switching mode converters and inverters for consumer, computer and telecommunication.



Mechanical Data

- **Package:** DO-201AD(DO-27)
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** Color band denotes the cathode end

■ Maximum Ratings (Ta=25°C Unless otherwise specified)

| PARAMETER | SYMBOL | UNIT | SF31G | SF32G | SF33G | SF34G | SF35G | SF36G | SF37G | SF38G |
|--|--------------------|------------------|------------|-------|-------|-------|-------|-------|-------|-------|
| Device marking code | | | SF31G | SF32G | SF33G | SF34G | SF35G | SF36G | SF37G | SF38G |
| Maximum Repetitive Peak Reverse Voltage | V _{RRM} | V | 50 | 100 | 150 | 200 | 300 | 400 | 500 | 600 |
| Maximum RMS Voltage | V _{RMS} | V | 35 | 70 | 105 | 140 | 210 | 280 | 350 | 420 |
| Maximum DC blocking Voltage | V _{DC} | V | 50 | 100 | 150 | 200 | 300 | 400 | 500 | 600 |
| Average Forward Current @60Hz sine wave, Resistance load, Ta =50°C | I _{F(AV)} | A | 3.0 | | | | | | | |
| Forward Surge Current (Non-repetitive) @60Hz Half-sine wave, 1 cycle, Tj=25°C | I _{FSM} | A | 125 | | | | | | | |
| Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, Tj=25°C | | | 250 | | | | | | | |
| Current squared time @1ms≤t≤8.3ms Tj=25°C, Rating of per diode | I ² t | A ² s | 65 | | | | | | | |
| Typical junction capacitance @Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C | C _j | pF | 62 | | | | 33 | | 30 | |
| Storage Temperature | T _{stg} | °C | -55 ~ +150 | | | | | | | |
| Junction Temperature | T _j | °C | -55 ~ +150 | | | | | | | |

■ Electrical Characteristics (Ta=25°C Unless otherwise specified)

| PARAMETER | SYMBOL | UNIT | TEST CONDITIONS | SF31G | SF32G | SF33G | SF34G | SF35G | SF36G | SF37G | SF38G |
|---|-----------------|------|---|-------|-------|-------|-------|-------|-------|-------|-------|
| Maximum instantaneous forward voltage drop per diode | V _F | V | I _{FM} =3.0A | 0.95 | | | | 1.3 | | 1.7 | |
| Maximum DC reverse current at rated DC blocking voltage per diode | I _R | μA | T _j =25°C | 2.5 | | | | | | | |
| | | | T _j =125°C | 100 | | | | | | | |
| Maximum reverse recovery time | t _{rr} | ns | I _F =0.5A, I _R =1.0A, I _r =0.25A | 35 | | | | | | | |



SF31G THRU SF38G

■ Thermal Characteristics (T_a=25°C Unless otherwise specified)

| PARAMETER | SYMBOL | UNIT | SF31G | SF32G | SF33G | SF34G | SF35G | SF36G | SF37G | SF38G |
|----------------------------|-------------------|------|-------|-------|-------|-------|-------|-------|-------|-------|
| Typical Thermal Resistance | R _{θJ-A} | °C/W | 30 | | | | | | | |

■ Ordering Information (Example)

| PREFERRED P/N | PACKAGE CODE | UNIT WEIGHT(g) | MINIMUM PACKAGE(pcs) | INNER BOX QUANTITY(pcs) | OUTER CARTON QUANTITY(pcs) | DELIVERY MODE |
|---------------|--------------|------------------|----------------------|-------------------------|----------------------------|---------------|
| SF31G~SF38G | D1 | Approximate 1.05 | 1250 | 1250 | 12500 | Tape |
| SF31G~SF38G | C1 | Approximate 1.05 | 250 | 250 | 12500 | Bulk |

■ Characteristics(Typical)

FIG.1: I_o-T_a Curve




FIG.2: Forward Surge Current Capability




FIG.3: Forward Voltage






FIG.4: Typical Reverse Characteristics






SF31G THRU SF38G

FIG.5: Diagram of circuit and Testing wave form of reverse recovery time



■ Outline Dimensions



| DO-201AD(DO-27) | | |
|-----------------|------|------|
| Dim | Min | Max |
| A | 8.50 | 9.50 |
| B | 5.00 | 5.60 |
| C | 25.4 | / |
| D | 1.20 | 1.30 |



SF31G THRU SF38G

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.