




US12-6-6-F

Ruland US12-6-6-F, 3/8" x 3/8" Single Universal Joint, Friction Bearing, Steel, 0.745" OD, 2.688" Length





Description

Ruland US12-6-6-F is a single cardan friction bearing universal joint with 0.3750" x 0.3750" bores, 0.745" OD, and 2.688" length. It is ideal for applications with space constraints and has higher torque capacity than equivalently sized double universal joints. This plain bearing universal joint is comprised of pins and blocks that are precision machined, selectively heat treated, and ground for high strength, accuracy, and wear resistance. The combination of these components with precision ground and hardened yoke ears allow for a longer lifespan, increased performance in demanding applications, and greater angular misalignment of up to 45° when compared to commodity style single universal joints. US12-6-6-F is made from high grade alloy steel for durability and high strength. It can be combined with boot UBOOT12/19-NI-KIT to protect the joint from unwanted contaminants such as dust or water and self lubricate reducing maintenance time. This single cardan universal joint is manufactured in the USA by Belden Universal for strict control of processes.

Product Specifications

Prop 65	▲WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov .		
Note 1	Performance ratings are for guidance only. The user must determine suitability for a particular application.		
UNSPC	25173810		
UPC	634529289518	Tariff Code	8483.60.4000
Recommended Lubricant	LUBRIPLATE No. 1200-2	Matching Boot Cover	UBOOT12/19-NI-KIT
Country of Origin	USA	Weight (lbs)	0.227000
Material Specification	Alloy Steel	Manufacturer	Belden Universal
Rated Torque	250 in-lb	Max Operating Angle	45°
Hub Depth (LH)	0.950 in	Peak Torque	1250 in-lb
Length (L)	2.688 in	Yoke Length (LY)	1.344 in
Joint Outer Diameter (OD)	0.745 in	Bore Tolerance	+0.0010 in / -0.0000 in
B1 Max Shaft Penetration	0.950 in	B2 Max Shaft Penetration	0.950 in
Bore (B1)	0.3750 in	Small Bore (B2)	0.3750 in