

# FSP600-80PSA(SK)



## FEATURES

- Certified CB 62368-1 & CB 60950-1
- Meet 80 Plus Bronze
- Design for 5,000 Meter above sea level
- High Reliability
- Low Ripple & Noise
- Over Current Protection
- Over Temperature Protection
- Over Voltage Protection

## SAFETY STANDARD APPROVAL



## DESCRIPTION

FSP600-80PSA(SK) is an industrial level of switching power supply. The power supply comes to offer the total power capacity up to 600 Watts, and provides optional -5V output features, which makes it to be perfectly used in an industrial environment. In addition, the power supply is ideally the best choice for workstation, communication or any other automation applications to use. The product also complies with the latest safety and EMC standards, which is perfectly to meet various regulations worldwide.

## GENERAL SPECIFICATIONS

|                        |  |               |  |
|------------------------|--|---------------|--|
| Dimension (L x W x H): | 140 x 150 x 86 (mm)<br>5.51 x 5.91 x 3.39 (inch) | Environment   | Working temperature: 0°C to 50°C<br>Storage temperature: -20°C to + 80°C<br>Working humidity: 85% RH non-condensing<br>Storage humidity: 95% RH non-condensing |
| Efficiency:            | 80 Plus Bronze                                   | MTBF:         | 100,000 hours of continuous operation at 25°C, Max,-output load  |
| Hold-up time:          | 115V / 60Hz: ≥ 16ms<br>230V / 50Hz: ≥ 16ms       | Applications: | Workstation ,Storage System ,IPC Controller  |
| Operating altitude:    | 5,000 meters above sea level                     |               |  |

## INPUT SPECIFICATIONS

|                  |                          |
|------------------|--------------------------|
| Input voltage:   | 90-264Vac                |
| Input frequency: | 47-63Hz                  |
| Input current:   | 115Vac @ 6A, 230Vac @ 3A |

## OUTPUT RATING

| Outputs      | +3.3V | +5V   | +12V1  | +12V2  | +12V3  | +12V4  | -12V   | +5Vsb | -5V*   |
|--------------|-------|-------|--------|--------|--------|--------|--------|-------|--------|
| Max.         | 25.0A | 25.0A | 16.0A  | 16.0A  | 16.0A  | 16.0A  | 0.5A   | 4.0A  | 0.1A   |
| Min.         | 0.0A  | 0.2A  | 0.05A  | 0.0A   | 0.0A   | 0.0A   | 0.0A   | 0.0A  | 0.0A   |
| Regulation   | ±5%   | ±5%   | ±5%    | ±5%    | ±5%    | ±5%    | ±10%   | ±5%   | ±10%   |
| Ripple/Noise | 50 mV | 50 mV | 120 mV | 120 mV | 120 mV | 120 mV | 120 mV | 50 mV | 100 mV |

The +3.3V and +5V total output shall not exceed 150W  
 \* -5V (Optional)

**MECHANICAL SPECIFICATIONS**

UNIT: mm [inch]

