

# TSA89

- 40GHz SOLUTIONS
- LOW LOSS/VSWR
- DOUBLE SHIELDED
- RUGGED COVER
- LIGHT WEIGHT



## TESTeLINK RF Cables



Professional High Frequency RF Test Cables.

Connector Choices Include;  
SMA, Type-N, 3.5mm, 2.92mm, & 2.4mm

Key Features;

- Hi-Frequency Point to Point Cable
- Light Weight Rugged Flexible Cable
- Low Loss <0.68db/ft @ 40GHz
- Low VSWR < 1.35:1 (Typical < 1.25:1)
- RF Leakage >-100dB to 18GHz
- Temp. Rated from -55°C to 125°C

### Configuration Chart

TSA89-D1D1-S24

TSA89-YYZZ-YYY

#### YYZZ = Connector Options

2.4mm Male (50GHz) = C1  
2.4mm Female (50GHz) = CF  
2.92mm Male (40GHz) = D1  
2.92mm Female (40GHz) = DF  
3.5mm Male (32GHz) = E1  
3.5mm Female (32GHz) = EF  
SMA Male = S1  
SMA Female = SF  
Type-N male = N1  
Type-N Female = NF

#### YYY = Length Options

FYY = Length in Feet(F06 = 6ft)  
SYY = Length in Inches(S18 = 18")  
YMY = Length in Meters(2M5 = 2.5m)  
CYY = Length in Centimeters(C30 = 30cm)

## TESTeLINK RF Cables