

3M™ UV Resistant Green Masking Tape

Technical Data Sheet



Description

Created for ultraviolet (UV) light resistance, this crepe paper tape removes cleanly from most surfaces with little to no edge residue for up to 14 days even after outdoor exposure. Choose this cost-effective solution for a wide variety of masking applications.

Key features

- UV resistance helps ensure reliable performance for up to 14 days outdoors
- Removes cleanly from most surfaces with little to no edge residue
- Strong hold adhesive adheres to a variety of substrates
- Product construction prevents paint infiltration to allow for crisp paint lines
- Easy unwind and hand tearability mean smooth application

Technical Information Notice

The following technical information and data should be considered representative or typical only and should not be used for specification purpose.

Product Construction

Backing: UV Resistant Crepe Paper

Adhesive Type: Rubber

Color: Green

Physical Properties

Property	Value	Test Method	Notes
Total Tape Thickness	4.8 mil (.12mm)	ASTM D3652	
Tensile Strength	33 N/cm (18 lb/in)	ASTM D3759	
180° Peel Adhesion	2.8 N/cm (25 oz/in)	ASTM D3330	
Elongation at Break	15%	ASTM D3759	
Short Term Temp Resistance	175°F (79°C)		

Roll Width and Length

3M™ UV Resistant Green Masking Tape are available in the following standards:

- Widths: 12mm, 18mm, 24mm, 36mm, 48mm, 72mm, 96mm
- Length: 55m
- Core size: 76.2 mm (3 in)
- Core Material: Paper

Storage and Shelf Life

Store under normal conditions of 70°F (21°C) 50% R.H. in the original carton. To obtain best performance, use this product within 12 months from date of manufacture.

Application Examples

- Paint masking for both indoor and outdoor applications
- Holding or protecting when outdoor weathering is encountered
- Protecting various items during painting and construction
- Holding temporary outdoor signs
- General outdoor use for periods not to exceed 14 days

Contact Information

The information provided in this technical document is intended as a guide for this product. For more information or help in selecting a 3M product for an application, please contact your 3M technical service representative or call 1-800-362-3550.

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com.



Closure and Masking Systems Division
3M Center
St. Paul, MN 55144-1000
Phone 1-800-362-3550
Web www.3M.com/masking

Issue date: 03/2023
Revision: 01

3M is a trademark of 3M Company
© 3M 2023. All rights reserved.