9 INCHES LENGTH



Connector A 132117RP SMA Jack Straight Brass Gold + Heatshrink 50 Ohm RG-316 Continuity/Hi-Pot Connector B 122192-15 TNC Jack Straight Bulkhead - Rear Mount Brass Nickel IP67 + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

| | Connector A | | | | Cable | | Connector B | | |
|--|-------------|-----------------------|--|---|-------------------------------------|--------------------------------|---------------------------------------|--|--|
| Part # | #: 1 | 132117RP | | Part #: | RG-316 | Part #: | 122192-15 | | |
| Desci | cription: S | SMA JACK RP RG316 500 | | Description: | RG-316 - ST 0.102 | Description: | TNC BHD JK RG174 RG188 RG316 IP67 500 | | |
| Type: | : S | SMA | | Dielectric: | ST | Туре: | TNC | | |
| Gend | der: J | Jack | | Shielding: | Braid | Gender: | Jack | | |
| Body | y Type: S | Straight | | Diameter: | 0.102 | Body Type: | Straight | | |
| Conta | tact Type: | Crimp | | Impedance: Sheathing: Testing: | 50 Ohm None Continuity Hi-Pot | Contact Type: | Crimp Standard 50 Ohm | | |
| Polar | rity: F | Reverse | | | | Polarity: | | | |
| Imped | edance: 5 | 50 Ohm | | | | Impedance: | | | |
| Moun | nting: C | Cable | | Length: | 9 Inches | Mounting: | Bulkhead - Rear Mo | unt | |
| | - | Brass | | Ū | | Body Material: | Brass | | |
| | | Gold | | | | Body Finish: | Nickel | | |
| IP Rai | | None | | | | IP Rating: | IP67 | | |
| | • | Brass | | | | Contact Material: | Phosphor Bronze | | |
| | | Gold | | | | Contact Finish: | Gold | | |
| | | 12.4 GHz | | | | Max. Freg.: | 11 GHz | | |
| Booti | • | SMA Jack Straight | t RP | | | Booting: | TNC Jack Straight BHD | | |
| | | | | | | Clocking: | 0° | | |
| | | | THIS DRAWING MAY CONTAIN | PATENTED OR | Title: | | | UNLESS SPECIFIED | |
| Amphenol FOR ANY PURPOSE DETRI INC. IT MAY NOT BE REPF | | | PROPRIETARY INFORMATION A FOR ANY PURPOSE DETRIMENT INC. IT MAY NOT BE REPRODUC IN ANY FORM WITHOUT THE W | ND MUST NOT BE US TAL TO CUSTOM CAE CED OR TRANSCRIBE | LE D | SMA-ST-JK-RP/TNC-ST-JK G316 9I | | TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: | |
| CONTROLLED DOCUMENT DO NOT CODY | | | CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING. | | NG Part No: | | | CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES | |



RoHS 2015/863 Compliance Statement

According to the manufacture of all the component parts contained in this assembly, this product has been determined to be RoHS Compliant with RoHS Directive 2011/65/EU and as amended by Directive 2015/863, and without material exceptions (RoHS3 Complaint).

For the individual component RoHS certificates used in this assembly, please contact Amphenol Custom Cable.

The RoHS Compliance of any product so designated is based upon evidence from the producer (manufacturers') that the component parts comply with the RoHS Directive. Amphenol Custom Cable has taken all reasonable steps to confirm that the OEM (Manufacturer) of the components used in this assembly have provided evidence regarding the absence of the restricted substances to support the manufacturer's claim of compliance.

To the best of our knowledge and with due diligence, we certify that the product listed herein complies with the RoHS requirements.

Date: 10/2/2023

Part Number: Q-7104E0005009I

Manufacturer: Amphenol Custom Cable

Description: SMA-ST-JK-RP/TNC-ST-JK G316 9I

This information is valid as of the date indicated for the item (part number) listed.

Director of Quality Assurance

Janice Frank