## Dimensions: [mm]


Impedance 010 MBr       Z       20.44k       10.00       0.       20.49k         Impedance 010 MBr       Z       20.44k       10.00       0.0       0.0         Impedance 010 MBr       Z       20.44k       10.00       0.0       0.0         Impedance 010 MBr       Z       20.44k       10.00       0.0       0.0       0.0         Impedance 010 MBr       Z       0.00       0.0					Properties		Test conditions	Value	Unit	Tol.
			-	<b>_</b>	Impedance @ 100 MHz			1000	Ω	±25%
32 ± 02       0       0       100			2,0	- <b>-</b>	Maximum Impedance	Z <sub>max</sub>	50 MHz	1500	Ω	typ.
32:02       0.5:40.3       0       0.5:40.3       0       0.5:40.3       0       100       0       0.5:40.3       0       100					Rated Current 1	I <sub>R 1</sub>	ΔT = 20 K	350	mA	max.
0.5 ± 0.3					Rated Current 2	I <sub>R 2</sub>	$\Delta T = 40 \text{ K}$	1100	mA	max.
0.5 ±0.3 3.2 ±0.2 3.2 ±0.2 3.2 ±0.2 3.2 ±0.2 5.2 ±					DC Resistance	R <sub>DC</sub>	@ 20 °C	0.5	Ω	max.
3.2 ±0.2       Cardian of based / HiGH SPEED: W = 4.2 HIGH CURRENT:       W = 4.2 W = 5.2         3.2 ±0.2       Image: State - 10:1         Image: State - 10:1       Image: State - 10:1         Image: State -					Туре		-	Wide Band	-	
3.2 ±0.2       Gentern at dataset (EC) 1907/2008         Halogen Free       Contorm of dataset (EC) 1907/2008         Component Qualification       AEC 0200 Grade 1         Schematic:       Schematic:         Schematic:       Centernal Information:         Component Qualification       AEC 0200 Grade 1         Schematic:       Centernal Information:         Schematic:       Centernal Information:         Component Qualification (a reginal component)       AEC 0200 Grade 1         Schematic:       Centernal Information:         Do not use this part boycod the Related Current as this will create excessive heat and can harm the component         Operating Temperature       -55 up to 1125 °C         Storage Conditions (in original component)       40°C (component)         Modeture Sensitivity Level (MSL)       1         Test conditions of Bactrical Proparties: +20°C, 33 % RH if not specified differently         Weiter Sensitivity Level (MSL)       1         Test conditions of Bactrical Proparties: +20°C, 33 % RH if not specified differently         Weiter Sensitivity Level (MSL)       1         Weiter Sensitivity Level (MSL)       1     <	0,5 ±0,3		WIDE BAND / HIGH SP HIGH CURRENT:			1				
Image: Scale - 101       Image: Scale - 101         Image: Scale -										
Scale - 10:1       Scale - 10:1       Hadges Pree       Contorm (EC 61249-2-21)         Schematic:       Schematic:       AcC-0200 Grade 1         Schematic:       Contours the fast of control to the fast of	<u>→ 3,2 ±0,2</u>								006]	
Schematic: Schemati										
Schematic: Schemati		<u>, 101</u>		Scale - 10:1						
Image: Scale - 10:1       Image: Scale - 10:1         Image: Scale - 10:1       Image: Scale - 10:1 <th></th> <th><u></u></th> <td></td> <td></td> <th>Component Qualification</th> <td></td> <td>AEC</td> <td>-Q200 Grade 1</td> <td></td> <td></td>		<u></u>			Component Qualification		AEC	-Q200 Grade 1		
$ \begin{array}{ c                                   $			Schemauc:	-	General Information					
Orgentiation       Component         Operating Temperature       -55 up to +125 °C         Storage Conditions (in original < 40 °C; < 75 %. RH         Moisture Sensitivity Level (MSL)       1         Test conditions of Electrical Properties: +20 °C, 33 % RH if not specified differently         Image: New York Sensitivity Level (MSL)       1         Image: New York										
Image: Second State of Sta	5	~		Do not use this part beyond the Rated Current as this will create excessive heat and can harm the component						
Image: Second State of Sta	0F			$\sim$	Operating Temperature		-55 up to +125 °C			
Scale - 10:1       Test conditions of Electrical Properties: +20 °C, 33 % RH if not specified differently         Image: Scale - 10:1       Image: Scale - 10:1         <	1.6	$\langle \rangle$					< 40 °C;< 75 % RH			
Scale - 10:1          With Eldentrik dog dirth 4 Co. KG         With Eldentrik dog dirth 4 Co.					Moisture Sensitivity Level (MSL)					
Image: Section with the section of the section with the section withe section with the section with the section					Test conditions of Electrical Properties: +20 °C, 33 % RH if not specified differently					
Image: Note: State of the		Scale - 10:1								
WÜRTH     Würth Elektronik elsos GmbH & Co. KG       MARGEN     Würth Elektronik elsos GmbH & Co. KG       Margen     Ustantian       Würth Elektronik elsos GmbH & Co. KG       Margen     Ustantian       Mürth Elektronik elsos GmbH & Co. KG       More THAN     Margen       Virth Elektronic elsos GmbH & Co. KG       Exc. & Inductive Solutions       Margen     Ustantian       Virth Elektronic elsos GmbH & Co. KG       Ender Margen     Exc. & Inductive Solutions       Margen     Ustantian       More THAN     Margen       VU EXPECT     Mitthelektronic elsos GmbH & Co. KG       More THAN     Margen       Margen								PROJECTION METHOD	$\square$	<u></u> ۔
WÜRTH ELEKTRONIK MORE THAN YOU EXPECT     EMC & Inductive Solutions 1/433     Ferrite Bead     ORDER CODE 742792161       Szzrtyfe     BUSNESS UNIT     STATUS     PAGE										
YOU EXPECT Tel. +49 (0) 79 42 945 - 0 www.we-online.com 1000			WÜRTH ELEKTRONIK		Ferrite Bead					
eiSos@we-online.com 1206 eiSos Valid 1/7				Tel. +49 (0) 79 42 945 - 0						
					1206		elSos	Valid		1/7

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is not authorized for use in equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik elSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in the require injury are deathing information. Functional control, train cont

## **Recommended Land Pattern: [mm]**

**Electrical Properties:** 

## Typical Impedance Characteristics:




This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Wurth Elektronik elSos GmbH & Co KG must be information intended for use in equipment where a higher safety standard and reliability standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Wurth Elektronik elSos GmbH & Co KG must be information intended for use in equivalent is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Wurth Elektronik elSos GmbH & Co KG must be information network etc.. Wurth Elektronik elSos GmbH & Co KG must be information intended for use in edicitability functions or performance.

**Derating Curve:** 

## Packaging Specification - Tape: [mm]

Packaging Specification - Reel: [mm]



This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Wurth Elektronik elSos GmbH & Co KG must be informed on every electronic component which is used in efficially governing such use, interview of use as even executed an agreement specifically governing such use. Moreover Wurth Elektronik elSos GmbH & Co KG must be information interview of acus severe personal injury or death, unless the parties have executed an agreement specifically governing such use, interview of issue and reliability transmotation (automotive control, transportation signal, disaster prevention, medical, public information network etc... Wurth Elektronik elSos GmbH & Co KG must be information entwork etc... Wurth Elektronic experiment on every electronic component which is used in efficient circuits every electral circuits etcel as efficient circuits every electral circuits etcel as efficient efficient efficient circuits every electral circuits etcel as efficient ef

Packaging Specification - Inner Carton: [mm] Packaging Specification - Outer Carton: [mm] Q ACT DI Т т W  $\mathcal{V}^{\mathsf{C}}$ С W  $\mathcal{V}^{\mathcal{V}}$ ∕℃ No. of Reel (pcs.) Qty. (pcs.) No. of Qty. (pcs.) W<sub>IC</sub> (mm) L<sub>IC</sub> (mm) H<sub>IC</sub> (mm) Material L<sub>C</sub> (mm) w<sub>c</sub> (mm) (mm) Material Inner Carton (pcs.) Tolerance typ. tvp. tvp. Tolerance typ. tvp typ. 185.00 150000 Value 185.00 Paper Value 445.00 210.00 Paper CHECKED REVISION DATE (YYYY-MM-DD) GENERAL TOLERANCE PROJECTION METHOD  $\oplus$ MBH 001.002 2020-10-14 DIN ISO 2768-1m 9 DESCRIPTION RoHS REACh HALOGEN 125 °C **WE-CBF SMT EMI Suppression** Würth Elektronik eiSos GmbH & Co. KG **Ferrite Bead** ORDER CODE WURTH EMC & Inductive Solutions Max-Eyth-Str. 1 742792161 ELEKTRONIK 74638 Waldenburg MORE THAN Germany SIZE/TYPE STATUS Tel. +49 (0) 79 42 945 - 0 BUSINESS UNIT PAGE YOU EXPECT www.we-online.com 4/7 1206 eiSos Valid eiSos@we-online.com

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Wurth Elektronik elSos GmbH & Co KG must be information intended for use in equipment where a higher safety standard and reliability standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Wurth Elektronik elSos GmbH & Co KG must be information intended for use in equivalent is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Wurth Elektronik elSos GmbH & Co KG must be information network etc.. Wurth Elektronik elSos GmbH & Co KG must be information intended for use in edicitability functions or performance.

## **Classification Reflow Profile for SMT components:**



## **Classification Reflow Soldering Profile:**

Profile Feature		Value
Preheat Temperature Min	T <sub>s min</sub>	150 °C
Preheat Temperature Max	T <sub>s max</sub>	200 °C
Preheat Time $t_s$ from $T_{s \min}$ to $T_{s \max}$	t <sub>s</sub>	60 - 120 seconds
Ramp-up Rate (T <sub>L</sub> to T <sub>P</sub> )		3 °C/ second max.
Liquidous Temperature	TL	217 °C
Time $\mathbf{t}_{\mathrm{L}}$ maintained above $\mathbf{T}_{\mathrm{L}}$	tL	60 - 150 seconds
Peak package body temperature	Т <sub>р</sub>	$T_p \leq T_c$ , see Table below
Time within 5°C of actual peak temperature	t p	20 - 30 seconds
Ramp-down Rate (T <sub>P</sub> to T <sub>L</sub> )		6 °C/ second max.
Time 25°C to peak temperature		8 minutes max.

refer to IPC/ JEDEC J-STD-020E

## Package Classification Reflow Temperature (T<sub>c</sub>):

Properties	Volume mm <sup>3</sup> <350	Volume mm <sup>3</sup> 350-2000	Volume mm <sup>3</sup> >2000
PB-Free Assembly I Package Thickness < 1.6 mm	260 °C	260 °C	260 °C
PB-Free Assembly I Package Thickness 1.6 mm - 2.5 mm	260 °C	250 °C	245 °C
PB-Free Assembly I Package Thickness > 2.5 mm	250 °C	245 °C	245 °C

refer to IPC/ JEDEC J-STD-020E

		CHECKED MBH	REVISION 001.002	DATE (YYYY-MM-DD) 2020-10-14	general tolerance DIN ISO 2768-1m		PROJECTION METHOD	-	<b>)</b> -		
			DESCRIPTION	F SMT I	EMI Suppre	ession					
	WÜRTH ELEKTRONIK HELEKTRONIK Kar-Syn-Str. 1 74638 Waldenburg			Ferrite	Bead			ORDER CODE	792161	1	
		MORE THAN YOU EXPECT	Germany Tel. +49 (0) (79 42 945 - 0 www.we-online.com eiSos@we-online.com	size/type 1206			BUSINESS UNIT eiSos	status Valid			page 5/7

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard and rel

## **Cautions and Warnings:**

# The following conditions apply to all goods within the product series of WE-CBF of Würth Elektronik eiSos GmbH & Co. KG:

#### **General:**

- This electronic component is designed and manufactured for use in general electronic equipment.
- Würth Elektronik must be asked for written approval (following the PPAP procedure) before incorporating the components into any
  equipment in fields such as military, aerospace, aviation, nuclear control, submarine, transportation (automotive control, train control,
  ship control), transportation signal, disaster prevention, medical, public information network, etc. where higher safety and reliability are
  especially required and/or if there is the possibility of direct damage or human injury.
- · Electronic components that will be used in safety-critical or high-reliability applications, should be pre-evaluated by the customer.
- The component is designed and manufactured to be used within the datasheet specified values. If the usage and operation conditions
  specified in the datasheet are not met, the component may be damaged or dissolved.
- Do not drop or impact the components, the component may be damaged.
- Würth Elektronik products are qualified according to international standards, which are listed in each product reliability report. Würth
  Elektronik does not warrant any customer qualified product characteristics beyond Würth Elektroniks' specifications, for its validity and
  sustainability over time.
- The responsibility for the applicability of the customer specific products and use in a particular customer design is always within the authority of the customer. All technical specifications for standard products also apply to customer specific products.

#### **Product specific:**

#### Soldering:

- The solder profile must comply with the technical product specifications. All other profiles will void the warranty. Wave soldering is allowed for components bigger than 0805 after evaluation and approval.
- All other soldering methods are at the customers' own risk.

#### **Cleaning and Washing:**

Washing agents used during the production to clean the customer application might damage or change the characteristics of the wire
insulation, marking or plating. Washing agents may have a negative effect on the long-term functionality of the product.

#### Potting:

If the product is potted in the customer application, the potting material might shrink or expand during and after hardening. Shrinking
could lead to an incomplete seal, allowing contaminants into the core. Expansion could damage the components. We recommend a
manual inspection after potting to avoid these effects.

#### **Storage Conditions:**

- A storage of Würth Elektronik products for longer than 12 months is not recommended. Within other effects, the terminals may suffer degradation, resulting in bad solderability. Therefore, all products shall be used within the period of 12 months based on the day of shipment.
- Do not expose the components to direct sunlight.
- The storage conditions in the original packaging are defined according to DIN EN 61760-2.
- The storage conditions stated in the original packaging apply to the storage time and not to the transportation time of the components.

#### Packaging:

 The packaging specifications apply only to purchase orders comprising whole packaging units. If the ordered quantity exceeds or is lower than the specified packaging unit, packaging in accordance with the packaging specifications cannot be ensured.

#### Handling:

- Violation of the technical product specifications such as exceeding the nominal rated current will void the warranty.
- The temperature rise of the component must be taken into consideration. The operating temperature is comprised of ambient temperature and temperature rise of the component. The operating temperature of the component shall not exceed the maximum temperature specified.

These cautions and warnings comply with the state of the scientific and technical knowledge and are believed to be accurate and reliable. However, no responsibility is assumed for inaccuracies or incompleteness.

			CHECKED MBH	REVISION 001.002	DATE (YYYY-MM-DD) 2020-10-14	GENERAL TOLERANCE DIN ISO 2768-1m		PROJECTION METHOD	=	<b>)</b> -
ROHS REACH HALOGEN 125 °C		WE-CBF SMT EMI Suppression								
WÜRTH ELEKTRONIK ELEKTRONIK 74638 Waldenburg			Ferrite	Bead			ORDER CODE	792161		
	MORE THAN YOU EXPECT	Germany Tel. +49 (0) 79 42 945 - 0 www.we-online.com elSos@we-online.com	size/type 1206			BUSINESS UNIT eiSos	status Valid		1	PAGE 6/7

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik elSos GmbH & Co KG must be informed on every electronic component which is used in areas such as military, aerospace, aviation, nuclear control, ship control, ship control, train control, tra

## **Important Notes**

## The following conditions apply to all goods within the product range of Würth Elektronik eiSos GmbH & Co. KG:

#### **1. General Customer Responsibility**

Some goods within the product range of Würth Elektronik eiSos GmbH & Co. KG contain statements regarding general suitability for certain application areas. These statements about suitability are based on our knowledge and experience of typical requirements concerning the areas, serve as general guidance and cannot be estimated as binding statements about the suitability for a customer application. The responsibility for the applicability and use in a particular customer design is always solely within the authority of the customer. Due to this fact it is up to the customer to evaluate, where appropriate to investigate and decide whether the device with the specific product characteristics described in the product specification is valid and suitable for the respective customer application or not.

#### 2. Customer Responsibility related to Specific, in particular Safety-Relevant Applications

It has to be clearly pointed out that the possibility of a malfunction of electronic components or failure before the end of the usual lifetime cannot be completely eliminated in the current state of the art, even if the products are operated within the range of the specifications. In certain customer applications requiring a very high level of safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health it must be ensured by most advanced technological aid of suitable design of the customer application that no injury or damage is caused to third parties in the event of malfunction or failure of an electronic component. Therefore, customer is cautioned to verify that data sheets are current before placing orders. The current data sheets can be downloaded at www.we-online.com.

#### 3. Best Care and Attention

Any product-specific notes, cautions and warnings must be strictly observed. Any disregard will result in the loss of warranty.

#### 4. Customer Support for Product Specifications

Some products within the product range may contain substances which are subject to restrictions in certain jurisdictions in order to serve specific technical requirements. Necessary information is available on request. In this case the field sales engineer or the internal sales person in charge should be contacted who will be happy to support in this matter.

#### 5. Product R&D

Due to constant product improvement product specifications may change from time to time. As a standard reporting procedure of the Product Change Notification (PCN) according to the JEDEC-Standard inform about minor and major changes. In case of further queries regarding the PCN, the field sales engineer or the internal sales person in charge should be contacted. The basic responsibility of the customer as per Section 1 and 2 remains unaffected.

#### 6. Product Life Cycle

Due to technical progress and economical evaluation we also reserve the right to discontinue production and delivery of products. As a standard reporting procedure of the Product Termination Notification (PTN) according to the JEDEC-Standard we will inform at an early stage about inevitable product discontinuance. According to this we cannot guarantee that all products within our product range will always be available. Therefore it needs to be verified with the field sales engineer or the internal sales person in charge about the current product availability expectancy before or when the product for application design-in disposal is considered. The approach named above does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.

#### 7. Property Rights

All the rights for contractual products produced by Würth Elektronik eiSos GmbH & Co. KG on the basis of ideas, development contracts as well as models or templates that are subject to copyright, patent or commercial protection supplied to the customer will remain with Würth Elektronik eiSos GmbH & Co. KG does not warrant or represent that any license, either expressed or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, application, or process in which Würth Elektronik eiSos GmbH & Co. KG components or services are used.

#### 8. General Terms and Conditions

Unless otherwise agreed in individual contracts, all orders are subject to the current version of the "General Terms and Conditions of Würth Elektronik eiSos Group", last version available at www.we-online.com.

			CHECKED MBH	REVISION 001.002	DATE (YYYY-MM-DD) 2020-10-14	GENERAL TOLERANCE DIN ISO 2768-1m	_	PROJECTION METHOD		<b>-</b>
		WE-CBF SMT EMI Suppression								
Würth Elektronik elöss GmbH & Co. KG EMC & Inductive Solutions Max-Eyth-Str. 1 74638 Waldenburg			Ferrite	Bead			ORDER CODE	792161		
	MORE THAN YOU EXPECT					BUSINESS UNIT eiSos	status Valid		1	PAGE 7/7

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik elSos GmbH & Co KG must be informed on every electronic component which is used in areas such as military, aerospace, aviation, nuclear control, ship control, ship control, train control, tra