



CORE DIMENSIONS				28T0375-300	
UNCOATED CORE					
	MM	INCHES		MM	INCHES
OD	9.53	(.375)	±	.25	(.010)
ID	4.75	(.187)	±	.25	(.010)
TH	4.78	(.188)	±	.13	(.005)

WEIGHT / K 1.2481 KGS 2.7515 LBS
 INITIAL PERMEABILITY 850

ROOM TEMPERATURE ELECTRICAL SPECIFICATION									
	MIN. TOL.	MIN. (μH)	NOM. (μH)	MAX. (μH)	MAX. TOL.	FREQ. (kHz)	VOLT. (mV)	GAUSS	URNS
L	-20.0%	0.45	0.565	0.68	20.0%	100	4.87	10	1
Q		4				100	4.87	10	1

NET IMPEDANCE					
	Min (Ω)	TOL	NOM (Ω)	Freq (MHz)	URNS
Z1 (REF.)	17.85	(-25%)	23.80	25	1
Z2	33.71	(-25%)	44.95	150	1

NOTES:



Rev	Description	Date	INT
E	Reactive the print, remove "P,Q,G,H" Spec	2009-6-23	Jcai

Date: 2009-6-23	DWG # 28T0375-300-E	Rev:
Drawn By: Jcai	Title # 28T0375-300	E

Steward This document contains information which is proprietary to Steward. No production or publication of this document in whole or in part shall be made without written authorization from Steward.

UNCONTROLLED DOCUMENT