



ALPHA & OMEGA
SEMICONDUCTOR

AON3818

24V Dual N-Channel α MOS™

General Description

- Trench Power α MOS™ LV technology
- Low $R_{DS(ON)}$
- Low Gate Charge
- ESD protection
- RoHS and Halogen-Free Compliant

Applications




- Battery protection switch
- Mobile device battery charging and discharging

Product Summary

V_{DS}	24V
I_D (at $V_{GS}=4.5V$)	8A
$R_{DS(ON)}$ (at $V_{GS}=4.5V$)	< 13.5mΩ
$R_{DS(ON)}$ (at $V_{GS}=4.0V$)	< 14mΩ
$R_{DS(ON)}$ (at $V_{GS}=3.7V$)	< 15mΩ
$R_{DS(ON)}$ (at $V_{GS}=3.1V$)	< 17mΩ
$R_{DS(ON)}$ (at $V_{GS}=2.5V$)	< 21mΩ

Typical ESD protection

HBM Class 2



Orderable Part Number	Package Type	Form	Minimum Order Quantity
AON3818	DFN 3x3	Tape & Reel	3000

Absolute Maximum Ratings $T_A=25^\circ\text{C}$ unless otherwise noted

Parameter	Symbol	Maximum		Units
Drain-Source Voltage	V_{DS}	24		V
Gate-Source Voltage	V_{GS}	± 12		V
Continuous Drain Current ^G	I_D	8		A
$T_A=70^\circ\text{C}$		6		
Pulsed Drain Current ^C	I_{DM}	32		
$T_A=25^\circ\text{C}$	P_D	2.7		W
$T_A=70^\circ\text{C}$		1.7		
Junction and Storage Temperature Range	T_J, T_{STG}	-55 to 150		°C

Thermal Characteristics

Parameter	Symbol	Typ	Max	Units
Maximum Junction-to-Ambient ^A	$R_{\theta JA}$	35	45	°C/W
Maximum Junction-to-Ambient ^{A,D} Steady-State		60	75	°C/W
Maximum Junction-to-Lead	$R_{\theta JL}$	15	20	°C/W

Electrical Characteristics ($T_J=25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
STATIC PARAMETERS						
BV_{DSS}	Drain-Source Breakdown Voltage	$I_D=250\mu\text{A}, V_{GS}=0\text{V}$	24			V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS}=24\text{V}, V_{GS}=0\text{V}$ $T_J=55^\circ\text{C}$		1	5	μA
I_{GSS}	Gate-Body leakage current	$V_{DS}=0\text{V}, V_{GS}=\pm 10\text{V}$			± 10	μA
$V_{GS(\text{th})}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu\text{A}$	0.4	0.8	1.2	V
$R_{DS(\text{ON})}$	Static Drain-Source On-Resistance	$V_{GS}=4.5\text{V}, I_D=8\text{A}$ $T_J=125^\circ\text{C}$	7.5	10.8	13.5	$\text{m}\Omega$
		$V_{GS}=4.0\text{V}, I_D=6\text{A}$	10.5	15	19	
		$V_{GS}=3.7\text{V}, I_D=6\text{A}$	7.8	11.2	14	
		$V_{GS}=3.1\text{V}, I_D=4\text{A}$	8	11.5	15	
		$V_{GS}=2.5\text{V}, I_D=4\text{A}$	8.6	12.5	17	
g_{FS}	Forward Transconductance	$V_{DS}=5\text{V}, I_D=8\text{A}$		42		S
V_{SD}	Diode Forward Voltage	$I_S=1\text{A}, V_{GS}=0\text{V}$		0.66	1	V
I_S	Maximum Body-Diode Continuous Current				4	A
DYNAMIC PARAMETERS						
C_{iss}	Input Capacitance	$V_{GS}=0\text{V}, V_{DS}=12\text{V}, f=1\text{MHz}$		840		pF
C_{oss}	Output Capacitance			210		pF
C_{rss}	Reverse Transfer Capacitance			205		pF
R_g	Gate resistance	f=1MHz		2		k Ω
SWITCHING PARAMETERS						
Q_g	Total Gate Charge	$V_{GS}=4.5\text{V}, V_{DS}=12\text{V}, I_D=8\text{A}$		9.5	15	nC
Q_{gs}	Gate Source Charge			1.5		nC
Q_{gd}	Gate Drain Charge			4.5		nC
$t_{D(\text{on})}$	Turn-On Delay Time	$V_{GS}=4.5\text{V}, V_{DS}=12\text{V}, R_L=1.5\Omega, R_{\text{GEN}}=3\Omega$		0.3		μs
t_r	Turn-On Rise Time			0.8		μs
$t_{D(\text{off})}$	Turn-Off Delay Time			1.7		μs
t_f	Turn-Off Fall Time			5.2		μs

A. The value of R_{iJA} is measured with the device mounted on 1in² FR-4 board with 2oz. Copper, in a still air environment with $T_A=25^\circ\text{C}$. The value in any given application depends on the user's specific board design.

B. The power dissipation P_0 is based on $T_{J(\text{MAX})}=150^\circ\text{C}$, using $\leq 10\text{s}$ junction-to-ambient thermal resistance.







C. Repetitive rating, pulse width limited by junction temperature $T_{J(\text{MAX})}=150^\circ\text{C}$. Ratings are based on low frequency and duty cycles to keep initial $T_J=25^\circ\text{C}$.






D. The R_{iJA} is the sum of the thermal impedance from junction to lead R_{iJL} and lead to ambient.




E. The static characteristics in Figures 1 to 6 are obtained using $<300\mu\text{s}$ pulses, duty cycle 0.5% max.

F. These curves are based on the junction-to-ambient thermal impedance which is measured with the device mounted on 1in² FR-4 board with 2oz. Copper, assuming a maximum junction temperature of $T_{J(\text{MAX})}=150^\circ\text{C}$. The SOA curve provides a single pulse rating.

APPLICATIONS OR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS

Figure 1: On-Region Characteristics (Note E)

Figure 2: Transfer Characteristics (Note E)

Figure 3: On-Resistance vs. Drain Current and Gate Voltage (Note E)

Figure 4: On-Resistance vs. Junction Temperature (Note E)

Figure 5: On-Resistance vs. Gate-Source Voltage (Note E)

Figure 6: Body-Diode Characteristics (Note E)

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS

Figure 7: Gate-Charge Characteristics

Figure 8: Capacitance Characteristics

Figure 9: Maximum Forward Biased Safe Operating Area (Note F)

Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note F)

Figure 11: Normalized Maximum Transient Thermal Impedance (Note F)

Gate Charge Test Circuit & Waveform

Resistive Switching Test Circuit & Waveforms

Unclamped Inductive Switching (UIS) Test Circuit & Waveforms

Diode Recovery Test Circuit & Waveforms
