

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Range Thalassa **Product name** Thalassa PLA **Enclosure type** Multi-purpose Product or component type Suitable enclosure PLA Version 750 mm Nominal height Nominal width 750 mm **Nominal depth Enclosure mounting** Floor-standing **Device composition** 1 top part 1 bottom part 2 side part 1 rear panel 1 door

		_	
Compl	leme	nta	rv/

Complemental y	
Body type	Sealed top and bottom part assembled with side parts
Door type	Transparent front
Number of doors	1 door(s)
Door opening side	Reversible (120 °)
Lock type	2 points lock, 5 mm double-bar
Accessibility for operation	Front Rear
Removable parts	Door by hinges Rear panel by fixing element
Material	Polyester reinforced with fibreglass
Colour	Grey (RAL 7035)
Standards	IEC 62208 UL 508 A
NEMA degree of protection	NEMA 1 NEMA 2 NEMA 12 NEMA 3S

NEMA 3 NEMA 3X NEMA 3R NEMA 13

	NEMA 5
Product certifications	Veritas UL/cUL listed DNV Marine
Electrical insulation class	Class II
Environment	
IP degree of protection	IP65 conforming to IEC 60529 (completely sealed)
IK degree of protection	IK08 conforming to IEC 62262 (glazed door)
Fire resistance	960 °C conforming to IEC 62208
Ambient air temperature for storage	-3590 °C
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	76.0 cm
Package 1 Width	78.0 cm
Package 1 Length	38.0 cm
Package 1 Weight	25.103 kg
Offer Sustainability	
Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes

Product out of China RoHS scope. Substance declaration for your information

China RoHS declaration

Product Environmental Profile

Recommended replacement(s)

China RoHS Regulation

RoHS exemption information

Environmental Disclosure