TechnologyPiezoII) All dimensions are in mm unless otherwise noted1Released from Engineering10/21/2013J.SResonant Frequency3,200(Hz)II </th <th></th> <th>5 → 150</th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th>		5 → 150									
DescriptionValueUnitNotesVersionDescriptionDateApprovTechnologyPiezo11 All dimensions are in mm unless otherwise noted1Released from Engineering10/21/2013J.SResonant Frequency3,200(Hz)2) All parts meet RoHS1Released from Engineering10/21/2013J.SRated Voltage12(V)SPL @ 10cm115(dBA)ToneDualMount TypeFlangeVoltage Range6 ~ 16(V)Max Rated Current65(mA)Housing MaterialABSStorage Temperature-20 ~ +60*C*CPiezo IndicatorPiezo IndicatorID/21/2013J.S10/21/2013J.S10/21/2013		UL1007 , AV	VG#24								
DescriptionValueUnitVersionDescriptionDateApprovTechnologyPiezo11) All dimensions are in mm unless otherwise noted1Released from Engineering10/21/2013J.SResonant Frequency3,200(Hz)2) All parts meet RoHS1 $Released from Engineering10/21/2013J.SRated Voltage12(V)$	Specifications			Notes			Revision History				
Resonant Frequency3,200(Hz)2) All parts meet ROHSIIIIRated Voltage12(V)SPL $@$ 10cm115(dBA)ToneDualIMount TypeFlangeIVoltage Range6 ~ 16(V)Max Rated Current65(mA)Housing MaterialABSIOperating Temperature-20 ~ +60°CStorage Temperature-20 ~ +60°CStorage Temperature-20 ~ +60°CPiezo IndicatorID/21/2013J.SDirateDirateDirateCLDirateCLDirateCLDirateCLDirateCLDirateCLDirateCLDirateCLDirateCLDirateCLDirateCLDirateCLDirateCLDirateDirateDirateCLDirateCLDirateDirateDirateCLDirateCLDirateDirateDirateCLDirateDirateDirateCLDirateDirateDirateCLDirateDirateDirateDirateDirateCLDirateDirateDirateDirateDirateDirateDirateCLDirateDirateDirate<	Description	Value	Unit			Version	Description				Approved
Rated Voltage12VSPL @ 10cm115(dBA)ToneDual $\begin{tabular}{lllllllllllllllllllllllllllllllllll$	Technology	Piezo			unless otherwise noted	1	Release	ed from Engi	neering	10/21/2013	J.S
SPL @ 10cm115(dBA)ToneDualIIIMount TypeFlangeIIVoltage Range $6 \sim 16$ (V)IIMax Rated Current65(mA)IIIHousing MaterialABSIIIIIOperating Temperature $-20 \sim +60$ °CPiezo IndicatorPiezo IndicatorIIPiezo IndicatorPiezo IndicatorPiezo IndicatorIIIIIIDotation10/21/2013C.E.10/21/2013J.S10/21/2013	Resonant Frequency	3,200	(Hz)	2) All parts meet RoHS							
ToneDualIMount TypeFlangeIMount Type $6 \sim 16$ (V)Voltage Range $6 \sim 16$ (V)Max Rated Current 65 (mA)Housing MaterialABSIOperating Temperature $-20 \sim +60$ °CStorage Temperature $-20 \sim +60$ °CPiezo IndicatorIIImage Dependence $10/21/2013$ J.SImage Dependence $10/21/$		12									
Mount TypeFlangeII <td>SPL @ 10cm</td> <td>115</td> <td>(dBA)</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>	SPL @ 10cm	115	(dBA)								
Voltage Range 6 ~ 16 (V) Max Rated Current 65 (mA) Housing Material ABS Image: Constraint of Constraints Image: Constraint of Constraints Image: Constraints <td>Tone</td> <td>Dual</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>	Tone	Dual									
Max Rated Current 65 (mA) Housing Material ABS Image: Constraint of the constraint	Mount Type	Flange									
Housing Material ABS Image: Constraint of the state	Voltage Range	6~16	(V)								
Operating Temperature -20 ~ +60 °C A.B. 10/21/2013 C.E. 10/21/2013 J.S 10/21/2013 Storage Temperature -20 ~ +60 °C Piezo Indicator ID503012-1 ID503012-1	Max Rated Current	65	(mA)								
Storage Temperature -20 ~ +60 °C Piezo Indicator ID503012_1	Housing Material	ABS				Drawn by	Date	Checked by	Date	Approved by	Date
	Operating Temperature	-20 ~ +60	°C			A.B.	10/21/2013	C.E.	10/21/2013	J.S	10/21/2013
					Piezo Indicator		IP503012-1				

Additional considerations can be found at www.dbunlimitedco.com/technical-articles.