



А

NOTES:

- I) "FCI", PART NUMBER AND DATE CODE TO BE MARKED ON THIS SURFACE.
 THE MARK CAN BE OMITTED IF THERE IS NOT ENOUGH SPACE ON THIS SURFACE.
- 2) MATERIALS:
 - -HOUSING GLASS FILLED WITH HIGH TEMP THERMOPLASTIC, UL94V-O.
 - -SIGNAL CONTACT COPPER ALLOY.
 - -POWER CONTACT HIGH CONDUCTIVITY COPPER ALLOY.
- 3) PLATING SPECIFICATION: 10116351
- 4) DENOTES CONNECTOR KEEP OUT ZONE.
- 5) DATUM AND BASIC DIMENIONS WERE ESTABLISHED BY CUSTOMER.
- 6) ALL HOLE DIAMETERS ARE FINISHED HOLE SIZES.
- 7) I.15 \pm 0.025MM DRILLED HOLE PLATED WITH 0.00762MM MIN Sn OVER 0.0254-0.0762MM Cu PLATING TO ACHIEVE A 1.02 \pm 0.07MM HOLE.
- 8) PRODUCT SPECIFICATION: GS-12-658.
 APPLICATION SPECIFICATION: GS-20-141.
 PRODUCT PACKAGE SPECIFICATION: GS-14-1502.
- 9) THE VOID CORING IN BETWEEN POWER MODULES, SIGNAL MODULES AND END MODULES ARE OPTIONAL AND THE SHAPE MAY BE DIFFERENT FOR OPTIMIZE THE MOLDING PROCESS. THE VOID CORING WILL NOT EFFECT TO PRODUCT FUNCTION.

元》

2015/05/12 projection size scale MMΑ3 e n q Zhen-Hua Liu 3:2 2015/07/17 \oplus Chr Fancy Zhang 2015/07/16 ecn no appr Pei-Ming Zhen PwrBlade+ rel level Released 2015/07/16 product family 15HP + 24S10106126-F006001 RA STB RECEPTACLE sheet 3 of 3 www.fci.com | cat. no. Product - Customer Drw

Pro/E File - REV C - 2009-06-09

3 PDS: Rev :A

STATUS:Released

Printed: Jul 20, 2015

D

right FCI

D