


1. Wiring Diagram.



2. Cable test condition :

- Open / Short : 100%
- Insulation resistance : 5M ohms
- Contact resistance : 2 ohm
- Hipot : DC 300V / 1 sec
- 3Each pcs with PE polybag.

5	CONN	USB3.0 A MAILE G/F BLUE	1	P2
4	PVC	45P PVC BLACK OVERMOLD	25g	
3	PE	LLDPE 500026 6201	16g	
2	CONN	USB3.0 A/M G/F BLUE	1	P1
1	CABLE	《28AWG (7/0.12TC) *P+D(7/0.10TC)+AL+M》*2+28AWG (7/0.12TC) *P+24AWG(7/0.2TC)*2C+A+D+B (96/0.12AM) OD5.5 BLACK	1	3000mm
NO. PART NO.		DESCRIPTION	QTY	UNIT/REF
		BILL OF MATERIAL		

A	INITIAL RELEASE	2014/08/28
REVECN#	DESCRIPTION	DATE
	Cnc Tech, LLC	
P/N:	103-1020-BL-00300	REV
TITLE	CABLE USB3.0 AM TO AM	
CUSTOMER P/N:		
CHECKED	DATE	
EDWIN	08/24/14	
CUSTOMER:		
APPROVAL		
SHEET	1 OF 1	