

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL RELEASE	12JUN2015	DL	CW
	B	ECR-20-014876	02JUN2021	WQR	CW
	BI	ECR-23-175264	15MAY2023	AC	CW

FOR "TI420246000-000"
COATED BOTH INSIDE AND OUTSIDE

4X M3 THREAD
4X M3 螺纹孔

SCALE 1:2

4- ϕ 4.4

开孔安装示意图
PANNEL CUT OUT

NOTES:

1. TECHNICAL CHARACTERISTICS:
BODY MATERIAL: DIE CAST ALUMINIUM ALLOY
SURFACE TREATMENT: POWDER-COATED, GRAY
DEGREE OF PROTECTION: IP65 (MATED)

注释:

1. 技术参数:
主体材料: 铝合金
表面处理: 粉末喷涂, 灰色
防护等级: IP65(配合)

4X ϕ 4.4

TI420246000-000	H24B-AG-BO	COATED BOTH INSIDE AND OUTSIDE
TI420240000-000		-
ASSEMBLY PART NUMBER	ASSEMBLY PART DESCRIPTION	REMARK

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	12JUN2015	STE TE Connectivity	
		DAVID LI	12JUN2015		
		CHK	CHRIS WANG		
		APVD	XU XIANG		
		PRODUCT SPEC	108-137013	NAME	H24B-AG-BO
		APPLICATION SPEC	114-137013	SIZE	A3
		WEIGHT	-	CAGE CODE	-
		CUSTOMER DRAWING		DRAWING NO	©-TI42024X000000
		SCALE	3:4	SHEET	1 OF 1
		REV	BI	RESTRICTED TO	-

1470-19 (3/13)